

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	18 Hour 45 Min 24 Sec
Total Counter :	4831086	Total Running Time :	2045 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.49	kN	No		
HEP :	25.0 %	17.78	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.44	kN	Yes 15	Times	
Ref :		14.22	kN			
LCP :	1.5 %	14.01	kN	Yes 15	Times	
LEP :	25.0 %	10.67	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.42	kN	Punch NO.;	48
SD :	1.20	%	Max :	1.51	kN	Punch NO.;	29
Mean Main Pressure :	14.25	kN	Min :	12.44	kN	Punch NO.;	19
SD :	4.70	%	Max :	15.73	kN	Punch NO.;	58
Filling Depth :	Increase ;	197	Times	Decrease ;	296	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	5.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.722	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.14	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	65
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	4831086	Tablets			
A.W.C Counter :	4809767	Tablets			
HEP :	442 (0.0%)	Tablets	LEP :	1611 (0.0%)	Tablets
GOOD :	4807714 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	18 Hour 45 Min 24 Sec
Total Counter :	4831086	Total Running Time :	2045 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.61	kN	No		
HEP :	25.0 %	17.90	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.53	kN	Yes 15	Times	
Ref :		14.32	kN			
LCP :	1.5 %	14.10	kN	Yes 15	Times	
LEP :	25.0 %	10.74	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	10.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.14	kN	Min :	1.09	kN	Punch NO.;	12
SD :	1.70	%	Max :	1.18	kN	Punch NO.;	76
Mean Main Pressure :	14.36	kN	Min :	13.26	kN	Punch NO.;	28
SD :	3.80	%	Max :	15.55	kN	Punch NO.;	73
Filling Depth :	Increase ;	133	Times	Decrease ;	159	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.27	mm
Filling Depth :	5.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.722	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.14	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	37
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	4831086	Tablets			
A.W.C Counter :	4809767	Tablets			
HEP :	442 (0.0%)	Tablets	LEP :	1611 (0.0%)	Tablets
GOOD :	4807714 (100.0%)	Tablets			