

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	20 Hour 23 Min 30 Sec
Total Counter :	5231474	Total Running Time :	2047 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.49	kN	No		
HEP :	25.0 %	17.78	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.44	kN	Yes 15	Times	
Ref :		14.22	kN			
LCP :	1.5 %	14.01	kN	Yes 15	Times	
LEP :	25.0 %	10.67	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.44	kN	Min :	1.40	kN	Punch NO.;	30
		1.40	%	Max :	1.50	kN	Punch NO.;	29
Mean Main Pressure :	SD :	14.29	kN	Min :	12.66	kN	Punch NO.;	7
		5.90	%	Max :	16.23	kN	Punch NO.;	73
Filling Depth :	Increase ;	236	Times	Decrease ;	325	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.754	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	66	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	69
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	5231474	Tablets			
A.W.C Counter :	5209469	Tablets			
HEP :	448 (0.0%)	Tablets	LEP :	1611 (0.0%)	Tablets
GOOD :	5207410 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	20 Hour 23 Min 30 Sec
Total Counter :	5231474	Total Running Time :	2047 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.61	kN	No		
HEP :	25.0 %	17.90	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	14.53	kN	Yes	15	Times
Ref :		14.32	kN			
LCP :	1.5 %	14.10	kN	Yes	15	Times
LEP :	25.0 %	10.74	kN	Yes	35	Rotations 35 Tablets
LSP :	30.0 %	10.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.15	kN	Min :	1.11	kN	Punch NO.;	30
SD :	1.50	%	Max :	1.19	kN	Punch NO.;	29
Mean Main Pressure :	14.27	kN	Min :	12.23	kN	Punch NO.;	46
SD :	4.40	%	Max :	15.83	kN	Punch NO.;	56
Filling Depth :	Increase ;	149	Times	Decrease ;	173	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.27	mm
Filling Depth :	5.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.754	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	66	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	40
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	5231474	Tablets			
A.W.C Counter :	5209469	Tablets			
HEP :	448 (0.0%)	Tablets	LEP :	1611 (0.0%)	Tablets
GOOD :	5207410 (100.0%)	Tablets			