

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	22 Hour 01 Min 30 Sec
Total Counter :	5631818	Total Running Time :	2048 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.71	kN	No		
HEP :	25.0 %	17.99	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.61	kN	Yes 15	Times	
Ref :		14.39	kN			
LCP :	1.5 %	14.17	kN	Yes 15	Times	
LEP :	25.0 %	10.79	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	10.07	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.44	kN	Min :	1.39	kN	Punch NO.;	66
SD :	1.30	%	Max :	1.49	kN	Punch NO.;	13
Mean Main Pressure :	14.43	kN	Min :	12.09	kN	Punch NO.;	13
SD :	5.40	%	Max :	16.44	kN	Punch NO.;	73
Filling Depth :	Increase ;	259	Times	Decrease ;	354	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	6.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	10
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	21
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	5631818	Tablets			
A.W.C Counter :	5609792	Tablets			
HEP :	448 (0.0%)	Tablets	LEP :	1612 (0.0%)	Tablets
GOOD :	5607732 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	22 Hour 01 Min 30 Sec
Total Counter :	5631818	Total Running Time :	2048 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.83	kN	No		
HEP :	25.0 %	18.11	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	14.70	kN	Yes 15	Times	
Ref :		14.49	kN			
LCP :	1.5 %	14.27	kN	Yes 15	Times	
LEP :	25.0 %	10.86	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	10.14	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.16	kN	Min :	1.13	kN	Punch NO.;	43
SD :	1.30	%	Max :	1.22	kN	Punch NO.;	17
Mean Main Pressure :	14.50	kN	Min :	12.59	kN	Punch NO.;	77
SD :	4.50	%	Max :	16.15	kN	Punch NO.;	73
Filling Depth :	Increase ;	167	Times	Decrease ;	194	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.27	mm
Filling Depth :	5.50	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	41
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	21
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	5631818	Tablets			
A.W.C Counter :	5609792	Tablets			
HEP :	448 (0.0%)	Tablets	LEP :	1612 (0.0%)	Tablets
GOOD :	5607732 (100.0%)	Tablets			