

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502850
Print Interval :	50000 Tablets	Running Time :	00 Hour 36 Min 42 Sec
Total Counter :	150172	Total Running Time :	2050 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.72	kN	No		
HEP :	25.0 %	16.08	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.05	kN	Yes 15	Times	
Ref :		12.86	kN			
LCP :	1.5 %	12.67	kN	Yes 15	Times	
LEP :	25.0 %	9.65	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.43	kN	Min :	1.39	kN	Punch NO.;	39
SD :	1.40	%	Max :	1.51	kN	Punch NO.;	17
Mean Main Pressure :	12.80	kN	Min :	11.56	kN	Punch NO.;	33
SD :	3.60	%	Max :	14.04	kN	Punch NO.;	56
Filling Depth :	Increase ;	328	Times	Decrease ;	398	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	5.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.669	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	55
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	37
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	69

Tablet Data (N/A)

Total Counter :	150172	Tablets			
A.W.C Counter :	145100	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	145077 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502850
Print Interval :	50000 Tablets	Running Time :	00 Hour 36 Min 42 Sec
Total Counter :	150172	Total Running Time :	2050 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.22	kN	No		
HEP :	25.0 %	15.60	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.67	kN	Yes 15	Times	
Ref :		12.48	kN			
LCP :	1.5 %	12.29	kN	Yes 15	Times	
LEP :	25.0 %	9.36	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.09	kN	Min :	1.05	kN	Punch NO.;	71
SD :	2.20	%	Max :	1.16	kN	Punch NO.;	17
Mean Main Pressure :	12.54	kN	Min :	10.85	kN	Punch NO.;	33
SD :	4.90	%	Max :	14.29	kN	Punch NO.;	56
Filling Depth :	Increase ;	204	Times	Decrease ;	214	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.27	mm
Filling Depth :	5.31	mm	Current Cam :	Cam B	
Main Air pressure :	0.669	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	62
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	37
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	69

Tablet Data (N/A)

Total Counter :	150172	Tablets			
A.W.C Counter :	145100	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	145077 (100.0%)	Tablets			