

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502850
Print Interval :	50000 Tablets	Running Time :	22 Hour 37 Min 56 Sec
Total Counter :	5553488	Total Running Time :	2072 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.36	kN	No		
HEP :	25.0 %	16.69	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.55	kN	Yes 15	Times	
Ref :		13.35	kN			
LCP :	1.5 %	13.15	kN	Yes 15	Times	
LEP :	25.0 %	10.01	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.44	kN	Min :	1.39	kN	Punch NO.;	26
SD :	1.70	%	Max :	1.51	kN	Punch NO.;	13
Mean Main Pressure :	13.23	kN	Min :	11.46	kN	Punch NO.;	19
SD :	6.10	%	Max :	14.89	kN	Punch NO.;	62
Filling Depth :	Increase ;	430	Times	Decrease ;	501	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.27	mm	Main Thickness ;	2.28	mm
Filling Depth :	5.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.732	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	65	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	22
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	5553488	Tablets			
A.W.C Counter :	5548038	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	176 (0.0%)	Tablets
GOOD :	5547857 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502850
Print Interval :	50000 Tablets	Running Time :	22 Hour 37 Min 56 Sec
Total Counter :	5553488	Total Running Time :	2072 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.49	kN	No		
HEP :	25.0 %	16.82	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.65	kN	Yes 15	Times	
Ref :		13.45	kN			
LCP :	1.5 %	13.25	kN	Yes 15	Times	
LEP :	25.0 %	10.09	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.17	kN	Min :	1.14	kN	Punch NO.;	16
		1.60	%	Max :	1.23	kN	Punch NO.;	17
Mean Main Pressure :		13.69	kN	Min :	11.26	kN	Punch NO.;	19
	SD :	4.80	%	Max :	15.10	kN	Punch NO.;	63
Filling Depth :	Increase ;	776	Times	Decrease ;	794	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.30	mm	Main Thickness ;	2.31	mm
Filling Depth :	5.39	mm	Current Cam :	Cam B	
Main Air pressure :	0.732	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	65	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	32
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.12	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	5553488	Tablets			
A.W.C Counter :	5548038	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	176 (0.0%)	Tablets
GOOD :	5547857 (100.0%)	Tablets			