

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 21 Sec
Total Counter :	100038	Total Running Time :	2075 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.77	kN	No		
HEP :	25.0 %	12.28	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	9.97	kN	Yes 15	Times	
Ref :		9.82	kN			
LCP :	1.5 %	9.68	kN	Yes 15	Times	
LEP :	25.0 %	7.37	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	6.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.84	kN	Min :	0.82	kN	Punch NO.;	33
SD :	1.00	%	Max :	0.86	kN	Punch NO.;	29
Mean Main Pressure :	10.02	kN	Min :	7.85	kN	Punch NO.;	17
SD :	10.50	%	Max :	11.92	kN	Punch NO.;	44
Filling Depth :	Increase ;	152	Times	Decrease ;	110	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	4.51	mm
Main Upper Punch Position ;	3.99	mm			
Main Lower Punch Position ;	6.50	mm	Main Thickness ;	2.51	mm
Filling Depth :	8.98	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.764	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	40
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.22	kN	Max Punch ;	47
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.17	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	100038	Tablets			
A.W.C Counter :	75678	Tablets			
HEP :	76 (0.1%)	Tablets	LEP :	296 (0.4%)	Tablets
GOOD :	75306 (99.5%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 21 Sec
Total Counter :	100038	Total Running Time :	2075 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.00	kN	No		
HEP :	25.0 %	12.50	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	10.15	kN	Yes	15	Times
Ref :		10.00	kN			
LCP :	1.5 %	9.85	kN	Yes	15	Times
LEP :	25.0 %	7.50	kN	Yes	35	Rotations 35 Tablets
LSP :	30.0 %	7.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.61	kN	Min :	0.60	kN	Punch NO.;	4
SD :	1.70	%	Max :	0.64	kN	Punch NO.;	28
Mean Main Pressure :	10.23	kN	Min :	9.11	kN	Punch NO.;	37
SD :	5.30	%	Max :	11.94	kN	Punch NO.;	8
Filling Depth :	Increase ;	115	Times	Decrease ;	116	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	4.01	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	3.99	mm			
Main Lower Punch Position ;	6.65	mm	Main Thickness ;	2.66	mm
Filling Depth :	8.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.764	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	40
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.22	kN	Max Punch ;	47
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.17	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	100038	Tablets			
A.W.C Counter :	75678	Tablets			
HEP :	76 (0.1%)	Tablets	LEP :	296 (0.4%)	Tablets
GOOD :	75306 (99.5%)	Tablets			