

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	01 Hour 34 Min 53 Sec
Total Counter :	150048	Total Running Time :	2075 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.39	kN	No		
HEP :	25.0 %	12.88	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	10.46	kN	Yes 15	Times	
Ref :		10.30	kN			
LCP :	1.5 %	10.15	kN	Yes 15	Times	
LEP :	25.0 %	7.73	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	7.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.83	kN	Min :	0.82	kN	Punch NO.;	19
SD :	0.90	%	Max :	0.86	kN	Punch NO.;	42
Mean Main Pressure :	10.01	kN	Min :	7.84	kN	Punch NO.;	11
SD :	10.10	%	Max :	12.12	kN	Punch NO.;	43
Filling Depth :	Increase ;	251	Times	Decrease ;	200	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	4.51	mm
Main Upper Punch Position ;	3.99	mm			
Main Lower Punch Position ;	6.50	mm	Main Thickness ;	2.51	mm
Filling Depth :	9.14	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	53
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.28	kN	Max Punch ;	44
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.28	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	150048	Tablets			
A.W.C Counter :	125657	Tablets			
HEP :	267 (0.2%)	Tablets	LEP :	445 (0.4%)	Tablets
GOOD :	124945 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	01 Hour 34 Min 53 Sec
Total Counter :	150048	Total Running Time :	2075 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.00	kN	No		
HEP :	25.0 %	12.50	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	10.15	kN	Yes 15	Times	
Ref :		10.00	kN			
LCP :	1.5 %	9.85	kN	Yes 15	Times	
LEP :	25.0 %	7.50	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	7.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.61	kN	Min :	0.59	kN	Punch NO.;	2
SD :	1.30	%	Max :	0.63	kN	Punch NO.;	27
Mean Main Pressure :	10.62	kN	Min :	9.48	kN	Punch NO.;	23
SD :	6.20	%	Max :	12.90	kN	Punch NO.;	39
Filling Depth :	Increase ;	187	Times	Decrease ;	187	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	4.01	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	3.99	mm			
Main Lower Punch Position ;	6.65	mm	Main Thickness ;	2.66	mm
Filling Depth :	8.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	53
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.28	kN	Max Punch ;	44
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.28	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	150048	Tablets			
A.W.C Counter :	125657	Tablets			
HEP :	267 (0.2%)	Tablets	LEP :	445 (0.4%)	Tablets
GOOD :	124945 (99.4%)	Tablets			