

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	03 Hour 09 Min 30 Sec
Total Counter :	300074	Total Running Time :	2077 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	98	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.39	kN	No		
HEP :	25.0 %	12.88	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	10.46	kN	Yes 15	Times	
Ref :		10.30	kN			
LCP :	1.5 %	10.15	kN	Yes 15	Times	
LEP :	25.0 %	7.73	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	7.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.95	kN	Punch NO.;	38
SD :	1.10	%	Max :	1.01	kN	Punch NO.;	47
Mean Main Pressure :	10.50	kN	Min :	8.57	kN	Punch NO.;	13
SD :	8.60	%	Max :	12.35	kN	Punch NO.;	38
Filling Depth :	Increase ; 529	Times	Decrease ;	471	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.50	mm
Filling Depth :	8.90	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	21
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	47
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	300074	Tablets			
A.W.C Counter :	274821	Tablets			
HEP :	474 (0.2%)	Tablets	LEP :	760 (0.3%)	Tablets
GOOD :	273587 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	03 Hour 09 Min 30 Sec
Total Counter :	300074	Total Running Time :	2077 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.44	kN	No		
HEP :	25.0 %	11.96	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	9.71	kN	Yes 15	Times	
Ref :		9.57	kN			
LCP :	1.5 %	9.43	kN	Yes 15	Times	
LEP :	25.0 %	7.18	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	6.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.76	kN	Min :	0.72	kN	Punch NO.;	38
SD :	1.90	%	Max :	0.79	kN	Punch NO.;	10
Mean Main Pressure :	9.73	kN	Min :	8.94	kN	Punch NO.;	5
SD :	5.00	%	Max :	10.90	kN	Punch NO.;	41
Filling Depth :	Increase ;	436	Times	Decrease ;	431	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	2.66	mm
Filling Depth :	8.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	21
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.18	kN	Max Punch ;	47
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	300074	Tablets			
A.W.C Counter :	274821	Tablets			
HEP :	474 (0.2%)	Tablets	LEP :	760 (0.3%)	Tablets
GOOD :	273587 (99.6%)	Tablets			