

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	sj97904	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	04 Hour 44 Min 06 Sec
Total Counter :	450112	Total Running Time :	2078 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.27	kN	No		
HEP :	25.0 %	13.72	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	11.20	kN	Yes 15	Times	
Ref :		10.98	kN			
LCP :	2.0 %	10.76	kN	Yes 15	Times	
LEP :	25.0 %	8.23	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	7.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.95	kN	Punch NO.;	14
SD :	1.20	%	Max :	1.01	kN	Punch NO.;	35
Mean Main Pressure :	11.13	kN	Min :	10.22	kN	Punch NO.;	28
SD :	4.50	%	Max :	12.84	kN	Punch NO.;	8
Filling Depth :	Increase ;	761	Times	Decrease ;	681	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.26	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	53
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	47
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	450112	Tablets			
A.W.C Counter :	424389	Tablets			
HEP :	694 (0.2%)	Tablets	LEP :	944 (0.2%)	Tablets
GOOD :	422751 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	sj97904	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	04 Hour 44 Min 06 Sec
Total Counter :	450112	Total Running Time :	2078 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.44	kN	No		
HEP :	25.0 %	11.96	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	9.76	kN	Yes 20	Times	
Ref :		9.57	kN			
LCP :	2.0 %	9.38	kN	Yes 20	Times	
LEP :	25.0 %	7.18	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	6.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.74	kN	Min :	0.71	kN	Punch NO.;	22
SD :	1.60	%	Max :	0.78	kN	Punch NO.;	31
Mean Main Pressure :	9.39	kN	Min :	8.38	kN	Punch NO.;	33
SD :	4.50	%	Max :	10.19	kN	Punch NO.;	6
Filling Depth :	Increase ;	604	Times	Decrease ;	611	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	2.66	mm
Filling Depth :	7.85	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	47
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	450112	Tablets			
A.W.C Counter :	424389	Tablets			
HEP :	694 (0.2%)	Tablets	LEP :	944 (0.2%)	Tablets
GOOD :	422751 (99.6%)	Tablets			