

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	sj97904	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	07 Hour 39 Min 14 Sec
Total Counter :	727846	Total Running Time :	2081 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.27	kN	No		
HEP :	25.0 %	13.72	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	11.20	kN	Yes 15	Times	
Ref :		10.98	kN			
LCP :	2.0 %	10.76	kN	Yes 15	Times	
LEP :	25.0 %	8.23	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	7.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.94	kN	Min :	0.92	kN	Punch NO.;	27
SD :	1.20	%	Max :	0.98	kN	Punch NO.;	47
Mean Main Pressure :	8.31	kN	Min :	6.36	kN	Punch NO.;	2
SD :	11.20	%	Max :	10.49	kN	Punch NO.;	40
Filling Depth :	Increase ;	1087	Times	Decrease ;	952	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	8.11	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.798	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.12	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.20	kN	Max Punch ;	47
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	727846	Tablets			
A.W.C Counter :	701737	Tablets			
HEP :	788 (0.1%)	Tablets	LEP :	1089 (0.2%)	Tablets
GOOD :	699860 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	sj97904	Batch NO. :	HAM2501050
Print Interval :	50000 Tablets	Running Time :	07 Hour 39 Min 14 Sec
Total Counter :	727846	Total Running Time :	2081 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.44	kN	No		
HEP :	25.0 %	11.96	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	9.76	kN	Yes 20	Times	
Ref :		9.57	kN			
LCP :	2.0 %	9.38	kN	Yes 20	Times	
LEP :	25.0 %	7.18	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	6.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.73	kN	Min :	0.71	kN	Punch NO.;	12
SD :	2.60	%	Max :	0.80	kN	Punch NO.;	47
Mean Main Pressure :	9.56	kN	Min :	7.42	kN	Punch NO.;	3
SD :	12.50	%	Max :	13.32	kN	Punch NO.;	17
Filling Depth :	Increase ;	827	Times	Decrease ;	821	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	2.66	mm
Filling Depth :	8.31	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.798	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	47
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.20	kN	Max Punch ;	47
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	727846	Tablets			
A.W.C Counter :	701737	Tablets			
HEP :	788 (0.1%)	Tablets	LEP :	1089 (0.2%)	Tablets
GOOD :	699860 (99.7%)	Tablets			