

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501150
Print Interval :	50000 Tablets	Running Time :	03 Hour 01 Min 17 Sec
Total Counter :	300106	Total Running Time :	2084 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.43	kN	No		
HEP :	25.0 %	13.88	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	11.33	kN	Yes 15	Times	
Ref :		11.10	kN			
LCP :	2.0 %	10.88	kN	Yes 15	Times	
LEP :	25.0 %	8.33	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	7.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	0.95	kN	Min :	0.93	kN	Punch NO.;	5
		0.80	%	Max :	0.96	kN	Punch NO.;	17
Mean Main Pressure :		11.28	kN	Min :	10.33	kN	Punch NO.;	41
	SD :	4.50	%	Max :	12.09	kN	Punch NO.;	39
Filling Depth :	Increase ;	1344	Times	Decrease ;	1161	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	2.45	mm
Filling Depth :	8.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	46
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	300106	Tablets			
A.W.C Counter :	295738	Tablets			
HEP :	383 (0.1%)	Tablets	LEP :	657 (0.2%)	Tablets
GOOD :	294698 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501150
Print Interval :	50000 Tablets	Running Time :	03 Hour 01 Min 17 Sec
Total Counter :	300106	Total Running Time :	2084 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.69	kN	No		
HEP :	25.0 %	12.20	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	9.95	kN	Yes 20	Times	
Ref :		9.76	kN			
LCP :	2.0 %	9.56	kN	Yes 20	Times	
LEP :	25.0 %	7.32	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	6.83	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.72	kN	Min :	0.70	kN	Punch NO.;	32
SD :	1.80	%	Max :	0.76	kN	Punch NO.;	51
Mean Main Pressure :	9.87	kN	Min :	8.87	kN	Punch NO.;	9
SD :	4.70	%	Max :	11.06	kN	Punch NO.;	26
Filling Depth :	Increase ;	976	Times	Decrease ;	934	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	2.66	mm
Filling Depth :	7.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	14
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	46
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	300106	Tablets			
A.W.C Counter :	295738	Tablets			
HEP :	383 (0.1%)	Tablets	LEP :	657 (0.2%)	Tablets
GOOD :	294698 (99.6%)	Tablets			