

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501250
Print Interval :	50000 Tablets	Running Time :	07 Hour 19 Min 17 Sec
Total Counter :	9094	Total Running Time :	2088 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.35	kN	No		
HEP :	25.0 %	12.83	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	10.47	kN	Yes 15	Times	
Ref :		10.27	kN			
LCP :	2.0 %	10.06	kN	Yes 15	Times	
LEP :	25.0 %	7.70	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	7.19	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.97	kN	Punch NO.;	4
SD :	0.90	%	Max :	1.01	kN	Punch NO.;	33
Mean Main Pressure :	10.23	kN	Min :	9.52	kN	Punch NO.;	10
SD :	4.20	%	Max :	11.31	kN	Punch NO.;	33
Filling Depth :	Increase ;	1698	Times	Decrease ;	1460	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	2.45	mm
Filling Depth :	8.38	mm	Current Cam :	Cam C	
Main Air pressure :	0.771	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	74	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	25
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	47
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	9094	Tablets			
A.W.C Counter :	5821	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	5820	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	rp98927	Batch NO. :	HAM2501250
Print Interval :	50000 Tablets	Running Time :	07 Hour 19 Min 17 Sec
Total Counter :	9094	Total Running Time :	2088 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	82	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.22	kN	No		
HEP :	25.0 %	11.75	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	9.59	kN	Yes 20	Times	
Ref :		9.40	kN			
LCP :	2.0 %	9.21	kN	Yes 20	Times	
LEP :	25.0 %	7.05	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	6.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.74	kN	Min :	0.72	kN	Punch NO.;	43
SD :	1.60	%	Max :	0.79	kN	Punch NO.;	3
Mean Main Pressure :	9.42	kN	Min :	8.72	kN	Punch NO.;	45
SD :	3.20	%	Max :	10.10	kN	Punch NO.;	2
Filling Depth :	Increase ;	1160	Times	Decrease ;	1088	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	2.66	mm
Filling Depth :	7.45	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.771	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	74	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	47
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	9094	Tablets			
A.W.C Counter :	5821	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	5820 (100.0%)	Tablets			