

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba800mg STJD1B00
User ID :	mr99799	Batch NO. :	JDM2501280
Print Interval :	50000 Tablets	Running Time :	00 Hour 44 Min 17 Sec
Total Counter :	73850	Total Running Time :	2098 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	165	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		120000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.91	kN	No		
HEP :	25.0 %	23.95	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	19.55	kN	Yes 15	Times	
Ref :		19.16	kN			
LCP :	2.0 %	18.78	kN	Yes 15	Times	
LEP :	25.0 %	14.37	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.41	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.09	kN	Punch NO.;	16
SD :	3.10	%	Max :	2.46	kN	Punch NO.;	23
Mean Main Pressure :	19.00	kN	Min :	17.85	kN	Punch NO.;	46
SD :	2.10	%	Max :	20.06	kN	Punch NO.;	2
Filling Depth :	Increase ; 21	Times	Decrease ; 24	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.61	mm
Filling Depth :	11.30	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.789	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	80	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	5
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	49
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	73850	Tablets			
A.W.C Counter :	70808	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	70808 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba800mg STJD1B00
User ID :	mr99799	Batch NO. :	JDM2501280
Print Interval :	50000 Tablets	Running Time :	00 Hour 44 Min 18 Sec
Total Counter :	73876	Total Running Time :	2098 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	30	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		120000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.56	kN	No		
HEP :	25.0 %	24.58	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.05	kN	Yes 20	Times	
Ref :		19.66	kN			
LCP :	2.0 %	19.27	kN	Yes 20	Times	
LEP :	25.0 %	14.75	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.84	kN	Punch NO.;	4
SD :	3.50	%	Max :	2.21	kN	Punch NO.;	23
Mean Main Pressure :	19.72	kN	Min :	18.86	kN	Punch NO.;	37
SD :	2.00	%	Max :	20.61	kN	Punch NO.;	50
Filling Depth :	Increase ; 6	Times	Decrease ; 15	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.73	mm	Main Thickness ;	4.74	mm
Filling Depth :	12.39	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.789	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	80	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	9
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	49
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	73876	Tablets			
A.W.C Counter :	70808	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	70808 (100.0%)	Tablets			