

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	am98755	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	01 Hour 54 Min 55 Sec
Total Counter :	300132	Total Running Time :	2100 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.64	kN	No		
HEP :	25.0 %	18.88	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	15.41	kN	Yes 15	Times	
Ref :		15.11	kN			
LCP :	2.0 %	14.81	kN	Yes 15	Times	
LEP :	25.0 %	11.33	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.02	kN	Min :	2.00	kN	Punch NO.;	6
		0.50	%	Max :	2.05	kN	Punch NO.;	25
Mean Main Pressure :		15.05	kN	Min :	13.91	kN	Punch NO.;	11
	SD :	3.40	%	Max :	16.18	kN	Punch NO.;	34
Filling Depth :	Increase ;	43	Times	Decrease ;	79	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.23	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.813	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.61	kN		
	Max ;	0.72	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	300132	Tablets			
A.W.C Counter :	292645	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	292642 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : am98755 Print Interval : 50000 Tablets Total Counter : 300132 Station : Station 2	Product Name : Tams0.4mg STUL2A00 Batch NO. : ULM2501904 Running Time : 01 Hour 54 Min 55 Sec Total Running Time : 2100 Hour 50 Min
--	--

Setting Value

Feeder :	Auto ;	74	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2400000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) :		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) :		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.66	kN	No		
HEP :	25.0 %	16.98	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	13.86	kN	Yes 20	Times	
Ref :		13.59	kN			
LCP :	2.0 %	13.32	kN	Yes 20	Times	
LEP :	25.0 %	10.19	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	9.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.23	kN	Min :	2.20	kN	Punch NO.;	36
		0.60	%	Max :	2.26	kN	Punch NO.;	15
Mean Main Pressure :		13.36	kN	Min :	11.01	kN	Punch NO.;	19
	SD :	5.50	%	Max :	15.20	kN	Punch NO.;	49
Filling Depth :	Increase ;	35	Times	Decrease ;	53	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.61	kN		
	Max ;	0.72	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	300132	Tablets			
A.W.C Counter :	292698	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	292695 (100.0%)	Tablets			