

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	pb97604	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	06 Hour 38 Min 10 Sec
Total Counter :	1050478	Total Running Time :	2105 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.94	kN	No		
HEP :	25.0 %	21.09	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	17.21	kN	Yes 15	Times	
Ref :		16.87	kN			
LCP :	2.0 %	16.54	kN	Yes 15	Times	
LEP :	25.0 %	12.66	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	11.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.71	kN	Min :	1.67	kN	Punch NO.;	12
		0.90	%	Max :	1.75	kN	Punch NO.;	23
Mean Main Pressure :		16.95	kN	Min :	14.74	kN	Punch NO.;	19
	SD :	4.00	%	Max :	18.21	kN	Punch NO.;	35
Filling Depth :	Increase ;	87	Times	Decrease ;	155	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.29	mm	Main Thickness ;	2.30	mm
Filling Depth :	8.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.787	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.32	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.33	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.29	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1050478	Tablets			
A.W.C Counter :	1041192	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1041187 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pb97604 Print Interval : 50000 Tablets Total Counter : 1050478 Station : Station 2	Product Name : Tams0.4mg STUL2A00 Batch NO. : ULM2501904 Running Time : 06 Hour 38 Min 10 Sec Total Running Time : 2105 Hour 34 Min
---	--

Setting Value

Feeder :	Auto ;	74	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2400000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.97	kN	No		
HEP :	25.0 %	20.16	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.45	kN	Yes 20	Times	
Ref :		16.13	kN			
LCP :	2.0 %	15.81	kN	Yes 20	Times	
LEP :	25.0 %	12.10	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.01	kN	Min :	1.96	kN	Punch NO.;	24
		0.90	%	Max :	2.05	kN	Punch NO.;	35
Mean Main Pressure :		16.25	kN	Min :	13.93	kN	Punch NO.;	19
	SD :	6.10	%	Max :	18.07	kN	Punch NO.;	34
Filling Depth :	Increase ;	98	Times	Decrease ;	132	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.45	mm	Pre Thickness ;	5.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.51	mm	Main Thickness ;	2.52	mm
Filling Depth :	8.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.787	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.28	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.33	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.29	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1050478	Tablets			
A.W.C Counter :	1041192	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1041187 (100.0%)	Tablets			