

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	pb97604	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	09 Hour 27 Min 53 Sec
Total Counter :	1500676	Total Running Time :	2108 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.20	kN	No		
HEP :	25.0 %	21.35	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	17.42	kN	Yes 15	Times	
Ref :		17.08	kN			
LCP :	2.0 %	16.74	kN	Yes 15	Times	
LEP :	25.0 %	12.81	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	11.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.68	kN	Min :	1.64	kN	Punch NO.;	13
		0.90	%	Max :	1.71	kN	Punch NO.;	40
Mean Main Pressure :		17.06	kN	Min :	15.96	kN	Punch NO.;	19
	SD :	3.50	%	Max :	18.63	kN	Punch NO.;	34
Filling Depth :	Increase ;	128	Times	Decrease ;	210	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.29	mm	Main Thickness ;	2.30	mm
Filling Depth :	8.12	mm	Current Cam :	Cam C	
Main Air pressure :	0.770	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.28	kN	Max Punch ;	23
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1500676	Tablets			
A.W.C Counter :	1491374	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1491364 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	pb97604	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	09 Hour 27 Min 53 Sec
Total Counter :	1500676	Total Running Time :	2108 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.68	kN	No		
HEP :	25.0 %	20.85	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	17.01	kN	Yes 20	Times	
Ref :		16.68	kN			
LCP :	2.0 %	16.35	kN	Yes 20	Times	
LEP :	25.0 %	12.51	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.87	kN	Min :	1.82	kN	Punch NO.;	49
SD :	1.20	%	Max :	1.94	kN	Punch NO.;	42
Mean Main Pressure :	16.85	kN	Min :	14.91	kN	Punch NO.;	1
SD :	4.70	%	Max :	18.48	kN	Punch NO.;	49
Filling Depth :	Increase ; 133	Times	Decrease ; 170	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.51	mm	Main Thickness ;	2.52	mm
Filling Depth :	8.21	mm	Current Cam :	Cam C	
Main Air pressure :	0.770	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.27	kN	Max Punch ;	31
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1500676	Tablets			
A.W.C Counter :	1491374	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1491364 (100.0%)	Tablets			