

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	sj97904	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 44 Sec
Total Counter :	1900852	Total Running Time :	2110 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2400000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.71	kN	No		
HEP :	25.0 %	20.87	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	17.03	kN	Yes 15	Times	
Ref :		16.70	kN			
LCP :	2.0 %	16.36	kN	Yes 15	Times	
LEP :	25.0 %	12.52	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	11.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.71	kN	Min :	1.68	kN	Punch NO.;	30
SD :	0.80	%	Max :	1.76	kN	Punch NO.;	42
Mean Main Pressure :	16.58	kN	Min :	14.77	kN	Punch NO.;	19
SD :	3.70	%	Max :	17.57	kN	Punch NO.;	26
Filling Depth :	Increase ;	135	Times	Decrease ;	219	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	8.16	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.783	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.27	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1900852	Tablets			
A.W.C Counter :	1891330	Tablets			
HEP :	14 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1891316 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : sj97904 Print Interval : 50000 Tablets Total Counter : 1900852 Station : Station 2	Product Name : Tams0.4mg STUL2A00 Batch NO. : ULM2501904 Running Time : 11 Hour 58 Min 44 Sec Total Running Time : 2110 Hour 55 Min
---	--

Setting Value

Feeder :	Auto ;	80	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		2400000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.75	kN	No		
HEP :	25.0 %	19.95	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.28	kN	Yes 20	Times	
Ref :		15.96	kN			
LCP :	2.0 %	15.64	kN	Yes 20	Times	
LEP :	25.0 %	11.97	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.89	kN	Min :	1.84	kN	Punch NO.;	5
		1.10	%	Max :	1.94	kN	Punch NO.;	25
Mean Main Pressure :		16.04	kN	Min :	14.00	kN	Punch NO.;	19
	SD :	5.00	%	Max :	17.81	kN	Punch NO.;	25
Filling Depth :	Increase ;	151	Times	Decrease ;	192	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	2.56	mm
Filling Depth :	8.23	mm	Current Cam :	Cam C	
				8.5-14mm	
Main Air pressure :	0.783	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.27	kN	Max Punch ;	33
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.15	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1900852	Tablets			
A.W.C Counter :	1891330	Tablets			
HEP :	14 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1891316 (100.0%)	Tablets			