

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	sj97904	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	13 Hour 51 Min 53 Sec
Total Counter :	2201034	Total Running Time :	2112 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.71	kN	No		
HEP :	25.0 %	20.87	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	17.03	kN	Yes 15	Times	
Ref :		16.70	kN			
LCP :	2.0 %	16.36	kN	Yes 15	Times	
LEP :	25.0 %	12.52	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	11.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.68	kN	Min :	1.66	kN	Punch NO.;	4
		0.70	%	Max :	1.71	kN	Punch NO.;	21
Mean Main Pressure :		17.07	kN	Min :	15.82	kN	Punch NO.;	11
	SD :	3.70	%	Max :	18.40	kN	Punch NO.;	26
Filling Depth :	Increase ;	149	Times	Decrease ;	220	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	8.63	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.28	kN	Max Punch ;	47
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	4
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	2201034	Tablets			
A.W.C Counter :	2191469	Tablets			
HEP :	14 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2191455 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Tams0.4mg STUL2A00
User ID :	sj97904	Batch NO. :	ULM2501904
Print Interval :	50000 Tablets	Running Time :	13 Hour 51 Min 53 Sec
Total Counter :	2201034	Total Running Time :	2112 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	76	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2400000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.75	kN	No		
HEP :	25.0 %	19.95	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.28	kN	Yes 20	Times	
Ref :		15.96	kN			
LCP :	2.0 %	15.64	kN	Yes 20	Times	
LEP :	25.0 %	11.97	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.83	kN	Punch NO.;	49
SD :	1.30	%	Max :	1.95	kN	Punch NO.;	41
Mean Main Pressure :	16.30	kN	Min :	14.22	kN	Punch NO.;	19
SD :	5.40	%	Max :	18.52	kN	Punch NO.;	14
Filling Depth :	Increase ;	172	Times	Decrease ;	211	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	2.56	mm
Filling Depth :	8.31	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.28	kN	Max Punch ;	32
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	4
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	2201034	Tablets			
A.W.C Counter :	2191469	Tablets			
HEP :	14 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2191455 (100.0%)	Tablets			