

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	rp98927	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	03 Hour 30 Min 11 Sec
Total Counter :	600314	Total Running Time :	2116 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.01	kN	No		
HEP :	25.0 %	18.28	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	14.92	kN	Yes 15	Times	
Ref :		14.63	kN			
LCP :	2.0 %	14.33	kN	Yes 15	Times	
LEP :	25.0 %	10.97	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.50	kN	Min :	2.43	kN	Punch NO.;	45
		1.20	%	Max :	2.58	kN	Punch NO.;	13
Mean Main Pressure :		14.69	kN	Min :	14.05	kN	Punch NO.;	45
	SD :	2.10	%	Max :	15.40	kN	Punch NO.;	61
Filling Depth :	Increase ;	0	Times	Decrease ;	6	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.75	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	9
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	56

Tablet Data (N/A)

Total Counter :	600314	Tablets			
A.W.C Counter :	596889	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	596889 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	rp98927	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	03 Hour 30 Min 11 Sec
Total Counter :	600314	Total Running Time :	2116 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.43	kN	No		
HEP :	25.0 %	18.69	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.25	kN	Yes 20	Times	
Ref :		14.95	kN			
LCP :	2.0 %	14.65	kN	Yes 20	Times	
LEP :	25.0 %	11.21	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.63	kN	Min :	2.54	kN	Punch NO.;	32
		1.40	%	Max :	2.70	kN	Punch NO.;	3
Mean Main Pressure :		15.02	kN	Min :	14.18	kN	Punch NO.;	6
	SD :	2.20	%	Max :	15.93	kN	Punch NO.;	61
Filling Depth :	Increase ;	0	Times	Decrease ;	3	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.92	mm
Filling Depth :	8.06	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	56

Tablet Data (N/A)

Total Counter :	600314	Tablets			
A.W.C Counter :	596889	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	596889 (100.0%)	Tablets			