

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	rp98927	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	03 Hour 47 Min 42 Sec
Total Counter :	650358	Total Running Time :	2117 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.01	kN	No		
HEP :	25.0 %	18.28	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	14.92	kN	Yes 15	Times	
Ref :		14.63	kN			
LCP :	2.0 %	14.33	kN	Yes 15	Times	
LEP :	25.0 %	10.97	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	10.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.45	kN	Punch NO.;	11
SD :	1.00	%	Max :	2.56	kN	Punch NO.;	9
Mean Main Pressure :	14.73	kN	Min :	14.20	kN	Punch NO.;	11
SD :	1.90	%	Max :	15.38	kN	Punch NO.;	25
Filling Depth :	Increase ; 0	Times	Decrease ; 6	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.75	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650358	Tablets			
A.W.C Counter :	646939	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	646939 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 400MG,STVI1B00
User ID :	rp98927	Batch NO. :	VIM2500940
Print Interval :	50000 Tablets	Running Time :	03 Hour 47 Min 42 Sec
Total Counter :	650358	Total Running Time :	2117 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.43	kN	No		
HEP :	25.0 %	18.69	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.25	kN	Yes 20	Times	
Ref :		14.95	kN			
LCP :	2.0 %	14.65	kN	Yes 20	Times	
LEP :	25.0 %	11.21	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.63	kN	Min :	2.53	kN	Punch NO.;	58
SD :	1.40	%	Max :	2.71	kN	Punch NO.;	25
Mean Main Pressure :	15.04	kN	Min :	14.40	kN	Punch NO.;	58
SD :	2.00	%	Max :	15.87	kN	Punch NO.;	61
Filling Depth :	Increase ; 0	Times	Decrease ; 3	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.92	mm
Filling Depth :	8.06	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650358	Tablets			
A.W.C Counter :	646939	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	646939 (100.0%)	Tablets			