

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	vg96371	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 37 Sec
Total Counter :	50038	Total Running Time :	2127 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.52	kN	No		
HEP :	25.0 %	25.50	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.81	kN	Yes 15	Times	
Ref :		20.40	kN			
LCP :	2.0 %	19.99	kN	Yes 15	Times	
LEP :	25.0 %	15.30	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.67	kN	Min :	3.54	kN	Punch NO.;	45
		1.60	%	Max :	3.79	kN	Punch NO.;	11
Mean Main Pressure :	SD :	20.80	kN	Min :	19.90	kN	Punch NO.;	32
		2.00	%	Max :	21.56	kN	Punch NO.;	11
Filling Depth :	Increase ;	14	Times	Decrease ;	22	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.59	mm	Current Cam :	Cam C	
Main Air pressure :	0.752	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.44	kN		
	Max ;	0.56	kN	Max Punch ;	25
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50038	Tablets			
A.W.C Counter :	46445	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46445 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	vg96371	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 37 Sec
Total Counter :	50038	Total Running Time :	2127 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.85	kN	No		
HEP :	25.0 %	25.82	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.07	kN	Yes 20	Times	
Ref :		20.66	kN			
LCP :	2.0 %	20.24	kN	Yes 20	Times	
LEP :	25.0 %	15.49	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.71	kN	Min :	3.56	kN	Punch NO.;	25
SD :	2.00	%	Max :	3.85	kN	Punch NO.;	12
Mean Main Pressure :	20.88	kN	Min :	19.51	kN	Punch NO.;	32
SD :	2.60	%	Max :	21.86	kN	Punch NO.;	12
Filling Depth :	Increase ;	10	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.60	mm
Filling Depth :	10.14	mm	Current Cam :	Cam C	
Main Air pressure :	0.752	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.45	kN		
	Max ;	0.57	kN	Max Punch ;	25
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50038	Tablets			
A.W.C Counter :	46445	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46445 (100.0%)	Tablets			