

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	os190259	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	10 Hour 39 Min 07 Sec
Total Counter :	1150392	Total Running Time :	2137 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	146	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.29	kN	No		
HEP :	25.0 %	25.27	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.62	kN	Yes 15	Times	
Ref :		20.22	kN			
LCP :	2.0 %	19.82	kN	Yes 15	Times	
LEP :	25.0 %	15.16	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.59	kN	Min :	3.47	kN	Punch NO.;	53
SD :	1.50	%	Max :	3.71	kN	Punch NO.;	48
Mean Main Pressure :	20.16	kN	Min :	19.10	kN	Punch NO.;	32
SD :	2.00	%	Max :	20.95	kN	Punch NO.;	48
Filling Depth :	Increase ; 145	Times	Decrease ;	139	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.19	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.46	mm
Filling Depth :	10.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.25	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	29
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1150392	Tablets			
A.W.C Counter :	1146064	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	73 (0.0%)	Tablets
GOOD :	1145983 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	os190259	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	10 Hour 39 Min 07 Sec
Total Counter :	1150392	Total Running Time :	2137 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	137	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.81	kN	No		
HEP :	25.0 %	27.70	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.61	kN	Yes 20	Times	
Ref :		22.16	kN			
LCP :	2.0 %	21.72	kN	Yes 20	Times	
LEP :	25.0 %	16.62	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.70	kN	Min :	3.49	kN	Punch NO.;	25
SD :	2.50	%	Max :	3.93	kN	Punch NO.;	46
Mean Main Pressure :	21.88	kN	Min :	20.70	kN	Punch NO.;	53
SD :	3.20	%	Max :	23.67	kN	Punch NO.;	46
Filling Depth :	Increase ;	117	Times	Decrease ;	138	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.19	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.61	mm
Filling Depth :	10.15	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.789	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.24	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	29
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1150392	Tablets			
A.W.C Counter :	1146064	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	73 (0.0%)	Tablets
GOOD :	1145983 (100.0%)	Tablets			