

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	sj97904	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	20 Hour 13 Min 25 Sec
Total Counter :	2241012	Total Running Time :	2146 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	146	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.27	kN	No		
HEP :	25.0 %	26.22	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.40	kN	Yes 15	Times	
Ref :		20.98	kN			
LCP :	2.0 %	20.56	kN	Yes 15	Times	
LEP :	25.0 %	15.73	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	14.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.18	kN	Min :	1.93	kN	Punch NO.;	47
SD :	19.00	%	Max :	3.39	kN	Punch NO.;	6
Mean Main Pressure :	8.21	kN	Min :	5.81	kN	Punch NO.;	43
SD :	52.30	%	Max :	18.89	kN	Punch NO.;	6
Filling Depth :	Increase ; 189	Times	Decrease ;	172	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.19	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.47	mm	Main Thickness ;	4.48	mm
Filling Depth :	10.92	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.36	kN	Max Punch ;	45
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	30
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2241012	Tablets			
A.W.C Counter :	2236275	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	247 (0.0%)	Tablets
GOOD :	2236020 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000 MG,STYQ1A00
User ID :	sj97904	Batch NO. :	YQM2501910
Print Interval :	50000 Tablets	Running Time :	20 Hour 13 Min 25 Sec
Total Counter :	2241012	Total Running Time :	2146 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	137	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2250000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.23	kN	No		
HEP :	25.0 %	27.15	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.15	kN	Yes 20	Times	
Ref :		21.72	kN			
LCP :	2.0 %	21.28	kN	Yes 20	Times	
LEP :	25.0 %	16.29	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.20	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.99	kN	Min :	2.55	kN	Punch NO.;	45
SD :	8.70	%	Max :	3.53	kN	Punch NO.;	26
Mean Main Pressure :	15.72	kN	Min :	11.76	kN	Punch NO.;	45
SD :	15.30	%	Max :	20.10	kN	Punch NO.;	30
Filling Depth :	Increase ;	171	Times	Decrease ;	184	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.19	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.63	mm	Main Thickness ;	4.64	mm
Filling Depth :	10.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.36	kN	Max Punch ;	45
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	30
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2241012	Tablets			
A.W.C Counter :	2236275	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	247 (0.0%)	Tablets
GOOD :	2236020 (100.0%)	Tablets			