

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pn98247	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 30 Sec
Total Counter :	1200282	Total Running Time :	2158 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.35	kN	No		
HEP :	25.0 %	24.38	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	19.89	kN	Yes 15	Times	
Ref :		19.50	kN			
LCP :	2.0 %	19.11	kN	Yes 15	Times	
LEP :	25.0 %	14.63	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	13.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.24	kN	Min :	3.08	kN	Punch NO.;	35
SD :	1.80	%	Max :	3.37	kN	Punch NO.;	12
Mean Main Pressure :	19.45	kN	Min :	18.49	kN	Punch NO.;	31
SD :	2.10	%	Max :	20.29	kN	Punch NO.;	12
Filling Depth :	Increase ; 261	Times	Decrease ;	264	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.39	mm	Main Thickness ;	4.40	mm
Filling Depth :	10.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	21
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1200282	Tablets			
A.W.C Counter :	1197729	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1197729 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pn98247	Batch NO. :	YQM2502110
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 30 Sec
Total Counter :	1200282	Total Running Time :	2158 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.92	kN	No		
HEP :	25.0 %	24.92	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.33	kN	Yes 20	Times	
Ref :		19.94	kN			
LCP :	2.0 %	19.54	kN	Yes 20	Times	
LEP :	25.0 %	14.95	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.42	kN	Min :	3.30	kN	Punch NO.;	35
SD :	2.00	%	Max :	3.60	kN	Punch NO.;	1
Mean Main Pressure :	19.78	kN	Min :	18.55	kN	Punch NO.;	53
SD :	3.20	%	Max :	21.33	kN	Punch NO.;	1
Filling Depth :	Increase ;	171	Times	Decrease ;	167	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.30	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.55	mm	Main Thickness ;	4.56	mm
Filling Depth :	10.22	mm	Current Cam :	Cam C	
				8.5-14mm	
Main Air pressure :	0.794	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	21
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1200282	Tablets			
A.W.C Counter :	1197729	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1197729 (100.0%)	Tablets			