

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502210
Print Interval :	50000 Tablets	Running Time :	07 Hour 53 Min 38 Sec
Total Counter :	800266	Total Running Time :	2177 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		25	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.31	kN	No		
HEP :	25.0 %	27.22	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.21	kN	Yes 15	Times	
Ref :		21.78	kN			
LCP :	2.0 %	21.34	kN	Yes 15	Times	
LEP :	25.0 %	16.33	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	15.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.86	kN	Min :	2.77	kN	Punch NO.;	35
SD :	1.50	%	Max :	2.99	kN	Punch NO.;	20
Mean Main Pressure :	21.75	kN	Min :	20.98	kN	Punch NO.;	25
SD :	1.90	%	Max :	22.98	kN	Punch NO.;	20
Filling Depth :	Increase ; 543	Times	Decrease ;	561	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	1.50	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	1.50	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	4.65	mm
Filling Depth :	10.06	mm	Current Cam :	Cam C	
Main Air pressure :	0.786	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	25
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	39
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	800266	Tablets			
A.W.C Counter :	790950	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	790950 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2502210
Print Interval :	50000 Tablets	Running Time :	07 Hour 53 Min 38 Sec
Total Counter :	800266	Total Running Time :	2177 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	148	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		25	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.09	kN	No		
HEP :	25.0 %	27.97	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.83	kN	Yes 20	Times	
Ref :		22.38	kN			
LCP :	2.0 %	21.93	kN	Yes 20	Times	
LEP :	25.0 %	16.78	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.66	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.06	kN	Min :	2.91	kN	Punch NO.;	35
		1.80	%	Max :	3.19	kN	Punch NO.;	1
Mean Main Pressure :	SD :	22.25	kN	Min :	20.99	kN	Punch NO.;	19
		2.70	%	Max :	23.86	kN	Punch NO.;	1
Filling Depth :	Increase ;	346	Times	Decrease ;	343	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	1.50	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	1.50	mm			
Main Lower Punch Position ;	6.20	mm	Main Thickness ;	4.70	mm
Filling Depth :	10.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.786	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	39
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	800266	Tablets			
A.W.C Counter :	790950	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	790950 (100.0%)	Tablets			