

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU 400MG STIU2B00    |
| User ID :        | rp98927       | Batch NO. :          | IUM2500740            |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 31 Min 38 Sec |
| Total Counter :  | 955048        | Total Running Time : | 2198 Hour 56 Min      |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |       |                      |
|------------------------------------|-------------|----------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ;      | 201      | %       | Manual ;           | 57    | RPM                  |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min : | 6.50 mm              |
| Target Quantity :                  |             | 8.5-14mm |         |                    | Max : | 12.00 mm             |
| Air Pressure Low Limit :           |             | 2025000  | Tablets |                    |       |                      |
| Oil Lubrication :                  |             | 0.400    | MPa     |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |             | 70       | Min     | Supply Time ;      | 1.0   | Sec                  |
| Lower Punch Interval Time(S2) ;    |             | 40       | Min     | Supply Time ;      | 2.0   | Sec                  |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |       |                      |
| Initial Reject Time :              |             | 2        | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |       |                      |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |       |                      |
|                                    |             |          |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 %      | 28.25    | kN      | No                 |       |                      |
| HEP :                              | 25.0 %      | 27.16    | kN      | Yes                | 10    | Rotations 20 Tablets |
| HCP :                              | 2.0 %       | 22.17    | kN      | Yes                | 15    | Times                |
| Ref :                              |             | 21.73    | kN      |                    |       |                      |
| LCP :                              | 2.0 %       | 21.30    | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 %      | 16.30    | kN      | No                 | 15    | Rotations 20 Tablets |
| LSP :                              | 30.0 %      | 15.21    | kN      | No                 |       |                      |
| SD limit :                         | 45.0 %      |          |         | Yes                |       |                      |
| Pre HSP                            |             | 40.00    | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | None        |          |         |                    |       |                      |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.51       | kN  | Min : | 2.41       | kN  | Punch NO.; | 36 |
| SD :                 | 1.50       | %   | Max : | 2.60       | kN  | Punch NO.; | 42 |
| Mean Main Pressure : | 21.65      | kN  | Min : | 20.60      | kN  | Punch NO.; | 36 |
| SD :                 | 2.40       | %   | Max : | 22.69      | kN  | Punch NO.; | 4  |
| Filling Depth :      | Increase ; | 177 | Times | Decrease ; | 127 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 40       | RPM          |
| Pre Upper Punch Position ;    | 2.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.30    | mm  | Pre Thickness ;  | 3.30     | mm           |
| Main Upper Punch Position ;   | 2.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.40    | mm  | Main Thickness ; | 2.40     | mm           |
| Filling Depth :               | 7.31    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.793   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 20      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 18      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.39 | kN | Max Punch ; | 5  |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.06 | kN | Max Punch ; | 42 |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 955048            | Tablets |       |           |         |
| A.W.C Counter : | 946746            | Tablets |       |           |         |
| HEP :           | 862 (0.1%)        | Tablets | LEP : | 73 (0.0%) | Tablets |
| GOOD :          | 945811<br>(99.9%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU 400MG STIU2B00    |
| User ID :        | rp98927       | Batch NO. :          | IUM2500740            |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 31 Min 38 Sec |
| Total Counter :  | 955048        | Total Running Time : | 2198 Hour 56 Min      |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 200      | %       | Manual ;           | 30           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 2025000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 70       | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 40       | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 60.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 27.47    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 26.41    | kN      | Yes 15             | Rotations 20 | Tablets   |
| HCP :                              | 2.0 %       | 21.55    | kN      | Yes 20             | Times        |           |
| Ref :                              |             | 21.13    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 20.71    | kN      | Yes 20             | Times        |           |
| LEP :                              | 25.0 %      | 15.85    | kN      | Yes 15             | Rotations 20 | Tablets   |
| LSP :                              | 30.0 %      | 14.79    | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 40.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N           |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.80       | kN  | Min : | 2.72       | kN  | Punch NO.; | 10 |
| SD :                 | 1.20       | %   | Max : | 2.87       | kN  | Punch NO.; | 5  |
| Mean Main Pressure : | 21.29      | kN  | Min : | 20.00      | kN  | Punch NO.; | 10 |
| SD :                 | 2.70       | %   | Max : | 22.41      | kN  | Punch NO.; | 40 |
| Filling Depth :      | Increase ; | 135 | Times | Decrease ; | 134 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 40       | RPM          |
| Pre Upper Punch Position ;    | 2.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.20    | mm  | Pre Thickness ;  | 3.20     | mm           |
| Main Upper Punch Position ;   | 2.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.53    | mm  | Main Thickness ; | 2.53     | mm           |
| Filling Depth :               | 7.42    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.793   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 20      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 18      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.39 | kN | Max Punch ; | 5  |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 42 |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 955048            | Tablets |       |           |         |
| A.W.C Counter : | 946746            | Tablets |       |           |         |
| HEP :           | 862 (0.1%)        | Tablets | LEP : | 73 (0.0%) | Tablets |
| GOOD :          | 945811<br>(99.9%) | Tablets |       |           |         |