

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	14 Hour 36 Min 26 Sec
Total Counter :	1855380	Total Running Time :	2206 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	201	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.00	kN	No		
HEP :	25.0 %	28.85	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	23.54	kN	Yes 15	Times	
Ref :		23.08	kN			
LCP :	2.0 %	22.62	kN	Yes 15	Times	
LEP :	25.0 %	17.31	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	16.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.39	kN	Punch NO.;	32
SD :	1.70	%	Max :	2.56	kN	Punch NO.;	6
Mean Main Pressure :	22.81	kN	Min :	21.40	kN	Punch NO.;	32
SD :	2.50	%	Max :	24.15	kN	Punch NO.;	8
Filling Depth :	Increase ; 331	Times	Decrease ;	271	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	3.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.42	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.39	kN	Max Punch ;	31
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1855380	Tablets			
A.W.C Counter :	1845703	Tablets			
HEP :	1060 (0.1%)	Tablets	LEP :	134 (0.0%)	Tablets
GOOD :	1844509 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400MG STIU2B00
User ID :	sj97904	Batch NO. :	IUM2500740
Print Interval :	50000 Tablets	Running Time :	14 Hour 36 Min 26 Sec
Total Counter :	1855380	Total Running Time :	2206 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.46	kN	No		
HEP :	25.0 %	27.37	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.33	kN	Yes 20	Times	
Ref :		21.89	kN			
LCP :	2.0 %	21.45	kN	Yes 20	Times	
LEP :	25.0 %	16.42	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.32	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.79	kN	Min :	2.73	kN	Punch NO.;	11
SD :	1.00	%	Max :	2.86	kN	Punch NO.;	4
Mean Main Pressure :	21.97	kN	Min :	20.86	kN	Punch NO.;	24
SD :	2.50	%	Max :	23.22	kN	Punch NO.;	22
Filling Depth :	Increase ; 237	Times	Decrease ;	250	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.53	mm
Filling Depth :	7.58	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.39	kN	Max Punch ;	31
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1855380	Tablets			
A.W.C Counter :	1845703	Tablets			
HEP :	1060 (0.1%)	Tablets	LEP :	134 (0.0%)	Tablets
GOOD :	1844509 (99.9%)	Tablets			