

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MIRTAZAPINE 15 MG
User ID :	rp98927	Batch NO. :	MRT TAB XV 25 001B
Print Interval :	50000 Tablets	Running Time :	01 Hour 04 Min 17 Sec
Total Counter :	200128	Total Running Time :	2208 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	57	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		513333	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.27	kN	No		
HEP :	25.0 %	11.80	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	9.63	kN	Yes 15	Times	
Ref :		9.44	kN			
LCP :	2.0 %	9.25	kN	Yes 15	Times	
LEP :	25.0 %	7.08	kN	No 15	Rotations 20	Tablets
LSP :	30.0 %	6.61	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.41	kN	Min :	2.34	kN	Punch NO.;	70
SD :	1.00	%	Max :	2.45	kN	Punch NO.;	1
Mean Main Pressure :	9.31	kN	Min :	9.05	kN	Punch NO.;	18
SD :	1.20	%	Max :	9.63	kN	Punch NO.;	51
Filling Depth :	Increase ; 4	Times	Decrease ;	12	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	4.50	mm			
Pre Lower Punch Position ;	6.65	mm	Pre Thickness ;	2.15	mm
Main Upper Punch Position ;	4.50	mm			
Main Lower Punch Position ;	6.35	mm	Main Thickness ;	1.85	mm
Filling Depth :	6.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.790	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.21	kN	Max Punch ;	62
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	63
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	200128	Tablets			
A.W.C Counter :	176067	Tablets			
HEP :	376 (0.2%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	175691 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MIRTAZAPINE 15 MG
User ID :	rp98927	Batch NO. :	MRT TAB XV 25 001B
Print Interval :	50000 Tablets	Running Time :	01 Hour 04 Min 17 Sec
Total Counter :	200128	Total Running Time :	2208 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		513333	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.40	kN	No		
HEP :	25.0 %	11.93	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	9.73	kN	Yes 20	Times	
Ref :		9.54	kN			
LCP :	2.0 %	9.35	kN	Yes 20	Times	
LEP :	25.0 %	7.16	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	6.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.47	kN	Min :	2.42	kN	Punch NO.;	56
SD :	1.00	%	Max :	2.54	kN	Punch NO.;	25
Mean Main Pressure :	9.48	kN	Min :	8.89	kN	Punch NO.;	63
SD :	2.50	%	Max :	10.06	kN	Punch NO.;	48
Filling Depth :	Increase ; 5	Times	Decrease ;	23	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	4.51	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	2.29	mm
Main Upper Punch Position ;	4.50	mm			
Main Lower Punch Position ;	6.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	6.31	mm	Current Cam :	Cam B	
Main Air pressure :	0.790	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.21	kN	Max Punch ;	62
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	61
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	200128	Tablets			
A.W.C Counter :	176067	Tablets			
HEP :	376 (0.2%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	175691 (99.8%)	Tablets			