

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	yu98249	Batch NO. :	XZM2500610
Print Interval :	50000 Tablets	Running Time :	01 Hour 37 Min 47 Sec
Total Counter :	250132	Total Running Time :	2211 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	6.37	kN	No		
HEP :	20.0 %	6.12	kN	Yes	10	Rotations 20 Tablets
HCP :	2.0 %	5.20	kN	Yes	15	Times
Ref :		5.10	kN			
LCP :	2.0 %	5.00	kN	Yes	15	Times
LEP :	20.0 %	4.08	kN	No	15	Rotations 20 Tablets
LSP :	25.0 %	3.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.38	kN	Punch NO.;	39
SD :	0.80	%	Max :	2.48	kN	Punch NO.;	30
Mean Main Pressure :	5.01	kN	Min :	4.96	kN	Punch NO.;	49
SD :	0.40	%	Max :	5.06	kN	Punch NO.;	59
Filling Depth :	Increase ;	8	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	7.64	mm	Current Cam :	Cam B	
Main Air pressure :	0.750	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.32	kN	Max Punch ;	24
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	250132	Tablets			
A.W.C Counter :	248504	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	248504 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	yu98249	Batch NO. :	XZM2500610
Print Interval :	50000 Tablets	Running Time :	01 Hour 37 Min 47 Sec
Total Counter :	250132	Total Running Time :	2211 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	6.79	kN	No		
HEP :	20.0 %	6.52	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	5.54	kN	Yes 20	Times	
Ref :		5.44	kN			
LCP :	2.0 %	5.33	kN	Yes 20	Times	
LEP :	20.0 %	4.35	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	4.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.54	kN	Min :	2.49	kN	Punch NO.;	48
SD :	1.00	%	Max :	2.60	kN	Punch NO.;	37
Mean Main Pressure :	5.44	kN	Min :	5.28	kN	Punch NO.;	41
SD :	0.90	%	Max :	5.55	kN	Punch NO.;	55
Filling Depth :	Increase ;	1	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.85	mm	Main Thickness ;	2.86	mm
Filling Depth :	7.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.750	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.31	kN	Max Punch ;	51
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	250132	Tablets			
A.W.C Counter :	248504	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	248504 (100.0%)	Tablets			