

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | OXAZEPAM 10<br>STXZ3B00 |
| User ID :        | rp98927       | Batch NO. :          | XZM2500710              |
| Print Interval : | 50000 Tablets | Running Time :       | 06 Hour 09 Min 07 Sec   |
| Total Counter :  | 1200568       | Total Running Time : | 2240 Hour 33 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 23                | %       | Manual ;           | 57           | RPM       |
| Filling Cam :                      |             | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |             | 4000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 35                | Min     | Supply Time ;      | 0.3          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 40                | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 %      | 5.57              | kN      | No                 |              |           |
| HEP :                              | 20.0 %      | 5.35              | kN      | Yes 10             | Rotations 20 | Tablets   |
| HCP :                              | 2.0 %       | 4.55              | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 4.46              | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 4.37              | kN      | Yes 15             | Times        |           |
| LEP :                              | 20.0 %      | 3.57              | kN      | No 15              | Rotations 20 | Tablets   |
| LSP :                              | 25.0 %      | 3.34              | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |               |       |              |       |    |            |    |
|----------------------|---------------|-------|--------------|-------|----|------------|----|
| Mean Pre Pressure :  | 2.23          | kN    | Min :        | 2.18  | kN | Punch NO.; | 39 |
| SD :                 | 0.70          | %     | Max :        | 2.27  | kN | Punch NO.; | 41 |
| Mean Main Pressure : | 4.43          | kN    | Min :        | 4.37  | kN | Punch NO.; | 28 |
| SD :                 | 0.40          | %     | Max :        | 4.49  | kN | Punch NO.; | 38 |
| Filling Depth :      | Increase ; 21 | Times | Decrease ; 1 | Times |    |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25     | RPM | Capacity :       | 195000   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 6        | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.99   | mm  | Pre Thickness ;  | 3.00     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.02   | mm  | Main Thickness ; | 3.03     | mm           |
| Filling Depth :               | 7.30   | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.799  | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 30     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 28     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.27 | kN |             |    |
|                  | Max ;     | 0.29 | kN | Max Punch ; | 14 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 37 |
| Ejection Force : | Average ; | 0.02 | kN |             |    |
|                  | Max ;     | 0.05 | kN | Max Punch ; | 41 |

### Tablet Data (N/A)

|                 |                     |         |       |        |         |
|-----------------|---------------------|---------|-------|--------|---------|
| Total Counter : | 1200568             | Tablets |       |        |         |
| A.W.C Counter : | 1196107             | Tablets |       |        |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 1196107<br>(100.0%) | Tablets |       |        |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | OXAZEPAM 10<br>STXZ3B00 |
| User ID :        | rp98927       | Batch NO. :          | XZM2500710              |
| Print Interval : | 50000 Tablets | Running Time :       | 06 Hour 09 Min 07 Sec   |
| Total Counter :  | 1200568       | Total Running Time : | 2240 Hour 33 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 25                | %       | Manual ;           | 30           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 4000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 35                | Min     | Supply Time ;      | 0.3          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40                | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 % | 5.88              | kN      | No                 |              |           |
| HEP :                              | 20.0 % | 5.65              | kN      | Yes 15             | Rotations 20 | Tablets   |
| HCP :                              | 2.0 %  | 4.80              | kN      | Yes 20             | Times        |           |
| Ref :                              |        | 4.71              | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 4.61              | kN      | Yes 20             | Times        |           |
| LEP :                              | 20.0 % | 3.77              | kN      | Yes 15             | Rotations 20 | Tablets   |
| LSP :                              | 25.0 % | 3.53              | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.24       | kN | Min : | 2.19       | kN | Punch NO.; | 41 |
| SD :                 | 0.70       | %  | Max : | 2.27       | kN | Punch NO.; | 31 |
| Mean Main Pressure : | 4.69       | kN | Min : | 4.59       | kN | Punch NO.; | 41 |
| SD :                 | 0.60       | %  | Max : | 4.76       | kN | Punch NO.; | 37 |
| Filling Depth :      | Increase ; | 26 | Times | Decrease ; | 38 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25     | RPM | Capacity :       | 195000   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 6        | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.30   | mm  | Pre Thickness ;  | 3.31     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 6.20   | mm  | Main Thickness ; | 3.21     | mm           |
| Filling Depth :               | 7.75   | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.799  | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 30     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 28     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.27 | kN |             |    |
|                  | Max ;     | 0.29 | kN | Max Punch ; | 14 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 37 |
| Ejection Force : | Average ; | 0.02 | kN |             |    |
|                  | Max ;     | 0.03 | kN | Max Punch ; | 43 |

### Tablet Data (N/A)

|                 |                     |         |       |        |         |
|-----------------|---------------------|---------|-------|--------|---------|
| Total Counter : | 1200568             | Tablets |       |        |         |
| A.W.C Counter : | 1196107             | Tablets |       |        |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 1196107<br>(100.0%) | Tablets |       |        |         |