

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	sj97904	Batch NO. :	XZM2500710
Print Interval :	50000 Tablets	Running Time :	14 Hour 20 Min 38 Sec
Total Counter :	2801434	Total Running Time :	2248 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	23	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	5.51	kN	No		
HEP :	20.0 %	5.29	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	4.50	kN	Yes 15	Times	
Ref :		4.41	kN			
LCP :	2.0 %	4.32	kN	Yes 15	Times	
LEP :	20.0 %	3.53	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	3.31	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.21	kN	Punch NO.;	20
SD :	0.60	%	Max :	2.27	kN	Punch NO.;	31
Mean Main Pressure :	4.44	kN	Min :	4.39	kN	Punch NO.;	47
SD :	0.40	%	Max :	4.48	kN	Punch NO.;	30
Filling Depth :	Increase ;	23	Times	Decrease ;	1	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.99	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.02	mm	Main Thickness ;	3.03	mm
Filling Depth :	7.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.785	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.29	kN	Max Punch ;	20
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	46
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.11	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	2801434	Tablets			
A.W.C Counter :	2796906	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2796906 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	OXAZEPAM 10 STXZ3B00
User ID :	sj97904	Batch NO. :	XZM2500710
Print Interval :	50000 Tablets	Running Time :	14 Hour 20 Min 38 Sec
Total Counter :	2801434	Total Running Time :	2248 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	5.90	kN	No		
HEP :	20.0 %	5.66	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	4.81	kN	Yes 20	Times	
Ref :		4.72	kN			
LCP :	2.0 %	4.63	kN	Yes 20	Times	
LEP :	20.0 %	3.78	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	3.54	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.22	kN	Min :	2.19	kN	Punch NO.;	2
SD :	0.60	%	Max :	2.26	kN	Punch NO.;	3
Mean Main Pressure :	4.70	kN	Min :	4.64	kN	Punch NO.;	28
SD :	0.50	%	Max :	4.81	kN	Punch NO.;	55
Filling Depth :	Increase ;	26	Times	Decrease ;	38	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.20	mm	Main Thickness ;	3.21	mm
Filling Depth :	7.71	mm	Current Cam :	Cam B	
Main Air pressure :	0.785	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.31	kN	Max Punch ;	48
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	46
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.11	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	2801434	Tablets			
A.W.C Counter :	2796906	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2796906 (100.0%)	Tablets			