

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LER HCL20MG STDJ1B00
User ID :	rp98927	Batch NO. :	DJM2500520
Print Interval :	50000 Tablets	Running Time :	00 Hour 47 Min 30 Sec
Total Counter :	100006	Total Running Time :	2255 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2550000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	12.33	kN	No		
HEP :	20.0 %	11.84	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	10.06	kN	Yes 15	Times	
Ref :		9.86	kN			
LCP :	2.0 %	9.67	kN	Yes 15	Times	
LEP :	20.0 %	7.89	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	7.40	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.61	kN	Min :	2.53	kN	Punch NO.;	20
SD :	1.20	%	Max :	2.68	kN	Punch NO.;	35
Mean Main Pressure :	9.77	kN	Min :	9.18	kN	Punch NO.;	18
SD :	2.90	%	Max :	10.43	kN	Punch NO.;	1
Filling Depth :	Increase ; 3	Times	Decrease ;	10	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.10	mm
Filling Depth :	5.35	mm	Current Cam :	Cam B	
Main Air pressure :	0.812	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.34	kN	Max Punch ;	51
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.19	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	100006	Tablets			
A.W.C Counter :	98418	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	98418 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LER HCL20MG STDJ1B00
User ID :	rp98927	Batch NO. :	DJM2500520
Print Interval :	50000 Tablets	Running Time :	00 Hour 47 Min 30 Sec
Total Counter :	100006	Total Running Time :	2255 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2550000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	12.84	kN	No		
HEP :	20.0 %	12.33	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	10.48	kN	Yes 20	Times	
Ref :		10.27	kN			
LCP :	2.0 %	10.07	kN	Yes 20	Times	
LEP :	20.0 %	8.22	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	7.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.78	kN	Min :	2.71	kN	Punch NO.;	53
SD :	1.30	%	Max :	2.88	kN	Punch NO.;	8
Mean Main Pressure :	10.27	kN	Min :	9.72	kN	Punch NO.;	15
SD :	2.80	%	Max :	10.99	kN	Punch NO.;	27
Filling Depth :	Increase ;	4	Times	Decrease ;	2	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.30	mm	Main Thickness ;	2.30	mm
Filling Depth :	5.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.812	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.35	kN	Max Punch ;	48
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.19	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	100006	Tablets			
A.W.C Counter :	98418	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	98418 (100.0%)	Tablets			