

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LER HCL20MG STDJ1B00
User ID :	rp98927	Batch NO. :	DJM2500520
Print Interval :	50000 Tablets	Running Time :	18 Hour 04 Min 41 Sec
Total Counter :	2516996	Total Running Time :	2272 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2550000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	12.87	kN	No		
HEP :	20.0 %	12.35	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	10.50	kN	Yes 15	Times	
Ref :		10.29	kN			
LCP :	2.0 %	10.09	kN	Yes 15	Times	
LEP :	20.0 %	8.23	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	7.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.35	kN	Min :	2.29	kN	Punch NO.;	53
SD :	1.00	%	Max :	2.40	kN	Punch NO.;	33
Mean Main Pressure :	10.14	kN	Min :	9.52	kN	Punch NO.;	18
SD :	3.00	%	Max :	10.87	kN	Punch NO.;	38
Filling Depth :	Increase ; 8	Times	Decrease ; 10	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.09	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.15	mm	Main Thickness ;	2.16	mm
Filling Depth :	5.71	mm	Current Cam :	Cam B	
Main Air pressure :	0.828	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.34	kN	Max Punch ;	34
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.17	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	2516996	Tablets			
A.W.C Counter :	2513842	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2513842 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LER HCL20MG STDJ1B00
User ID :	rp98927	Batch NO. :	DJM2500520
Print Interval :	50000 Tablets	Running Time :	18 Hour 04 Min 41 Sec
Total Counter :	2516996	Total Running Time :	2272 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2550000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		35	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	12.86	kN	No		
HEP :	20.0 %	12.34	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	10.49	kN	Yes 20	Times	
Ref :		10.29	kN			
LCP :	2.0 %	10.08	kN	Yes 20	Times	
LEP :	20.0 %	8.23	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	7.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.54	kN	Min :	2.36	kN	Punch NO.;	29
SD :	2.40	%	Max :	2.64	kN	Punch NO.;	33
Mean Main Pressure :	9.91	kN	Min :	8.81	kN	Punch NO.;	9
SD :	4.50	%	Max :	10.72	kN	Punch NO.;	25
Filling Depth :	Increase ;	12	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.08	mm	Pre Thickness ;	3.09	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.37	mm	Main Thickness ;	2.38	mm
Filling Depth :	6.53	mm	Current Cam :	Cam B	
Main Air pressure :	0.828	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.34	kN	Max Punch ;	34
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	2516996	Tablets			
A.W.C Counter :	2513842	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2513842 (100.0%)	Tablets			