

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	rp98927	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	06 Hour 28 Min 16 Sec
Total Counter :	1250636	Total Running Time :	2279 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.54	kN	No		
HEP :	20.0 %	9.16	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	7.75	kN	Yes 15	Times	
Ref :		7.63	kN			
LCP :	1.5 %	7.52	kN	Yes 15	Times	
LEP :	20.0 %	6.11	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.52	kN	Min :	1.38	kN	Punch NO.;	24
SD :	3.10	%	Max :	1.60	kN	Punch NO.;	35
Mean Main Pressure :	7.61	kN	Min :	5.42	kN	Punch NO.;	27
SD :	9.60	%	Max :	8.70	kN	Punch NO.;	16
Filling Depth :	Increase ; 56	Times	Decrease ;	108	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.821	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	57	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.38	kN	Max Punch ;	17
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	24
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	1250636	Tablets			
A.W.C Counter :	1234244	Tablets			
HEP :	591 (0.0%)	Tablets	LEP :	10834 (0.9%)	Tablets
GOOD :	1222819 (99.1%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	rp98927	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	06 Hour 28 Min 16 Sec
Total Counter :	1250636	Total Running Time :	2279 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.91	kN	No		
HEP :	20.0 %	9.52	kN	Yes 15	Rotations 20	Tablets
HCP :	1.5 %	8.05	kN	Yes 20	Times	
Ref :		7.93	kN			
LCP :	1.5 %	7.81	kN	Yes 20	Times	
LEP :	20.0 %	6.34	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	5.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.76	kN	Min :	1.65	kN	Punch NO.;	55
SD :	2.10	%	Max :	1.85	kN	Punch NO.;	46
Mean Main Pressure :	7.97	kN	Min :	6.50	kN	Punch NO.;	55
SD :	5.30	%	Max :	8.95	kN	Punch NO.;	46
Filling Depth :	Increase ;	132	Times	Decrease ;	150	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	3.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.821	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	57	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.39	kN	Max Punch ;	15
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	24
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	1250636	Tablets			
A.W.C Counter :	1234309	Tablets			
HEP :	591 (0.0%)	Tablets	LEP :	10834 (0.9%)	Tablets
GOOD :	1222884 (99.1%)	Tablets			