

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	ks99394	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	12 Hour 06 Min 26 Sec
Total Counter :	2351218	Total Running Time :	2284 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.53	kN	No		
HEP :	20.0 %	9.15	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	7.74	kN	Yes 15	Times	
Ref :		7.63	kN			
LCP :	1.5 %	7.51	kN	Yes 15	Times	
LEP :	20.0 %	6.10	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.60	kN	Min :	1.42	kN	Punch NO.;	49
		3.80	%	Max :	1.72	kN	Punch NO.;	2
Mean Main Pressure :	SD :	7.62	kN	Min :	5.29	kN	Punch NO.;	49
		10.00	%	Max :	9.12	kN	Punch NO.;	2
Filling Depth :	Increase ;	80	Times	Decrease ;	148	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.63	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	80	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	9
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	24
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	2351218	Tablets			
A.W.C Counter :	2333694	Tablets			
HEP :	878 (0.0%)	Tablets	LEP :	41082 (1.8%)	Tablets
GOOD :	2291734 (98.2%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	ks99394	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	12 Hour 06 Min 26 Sec
Total Counter :	2351218	Total Running Time :	2284 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.92	kN	No		
HEP :	20.0 %	9.52	kN	Yes	15	Rotations
HCP :	1.5 %	8.05	kN	Yes	20	Times
Ref :		7.93	kN			
LCP :	1.5 %	7.82	kN	Yes	20	Times
LEP :	20.0 %	6.35	kN	Yes	15	Rotations
LSP :	25.0 %	5.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.85	kN	Min :	1.75	kN	Punch NO.;	55
SD :	1.70	%	Max :	1.91	kN	Punch NO.;	1
Mean Main Pressure :	8.08	kN	Min :	6.61	kN	Punch NO.;	55
SD :	5.10	%	Max :	8.91	kN	Punch NO.;	2
Filling Depth :	Increase ;	219	Times	Decrease ;	240	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	4.03	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	80	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	24
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	2351218	Tablets			
A.W.C Counter :	2333759	Tablets			
HEP :	878 (0.0%)	Tablets	LEP :	41082 (1.8%)	Tablets
GOOD :	2291799 (98.2%)	Tablets			