

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	17 Hour 30 Min 49 Sec
Total Counter :	3402060	Total Running Time :	2290 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.87	kN	No		
HEP :	20.0 %	9.47	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	8.01	kN	Yes 15	Times	
Ref :		7.89	kN			
LCP :	1.5 %	7.77	kN	Yes 15	Times	
LEP :	20.0 %	6.31	kN	No 15	Rotations 20	Tablets
LSP :	25.0 %	5.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.68	kN	Min :	1.55	kN	Punch NO.;	26
SD :	3.40	%	Max :	1.84	kN	Punch NO.;	2
Mean Main Pressure :	7.94	kN	Min :	6.36	kN	Punch NO.;	49
SD :	8.20	%	Max :	9.57	kN	Punch NO.;	2
Filling Depth :	Increase ;	137	Times	Decrease ;	198	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	11
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	3402060	Tablets			
A.W.C Counter :	3369863	Tablets			
HEP :	1645 (0.0%)	Tablets	LEP :	63930 (1.9%)	Tablets
GOOD :	3304288 (98.1%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	pb97604	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	17 Hour 30 Min 49 Sec
Total Counter :	3402060	Total Running Time :	2290 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	31	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	9.76	kN	No		
HEP :	20.0 %	9.37	kN	Yes 15	Rotations 20	Tablets
HCP :	1.5 %	7.92	kN	Yes 20	Times	
Ref :		7.81	kN			
LCP :	1.5 %	7.69	kN	Yes 20	Times	
LEP :	20.0 %	6.24	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	5.85	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.84	kN	Min :	1.77	kN	Punch NO.;	51
SD :	1.60	%	Max :	1.90	kN	Punch NO.;	41
Mean Main Pressure :	7.64	kN	Min :	6.40	kN	Punch NO.;	51
SD :	5.20	%	Max :	8.33	kN	Punch NO.;	2
Filling Depth :	Increase ;	297	Times	Decrease ;	321	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	4.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	18
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	3402060	Tablets			
A.W.C Counter :	3369863	Tablets			
HEP :	1645 (0.0%)	Tablets	LEP :	63930 (1.9%)	Tablets
GOOD :	3304288 (98.1%)	Tablets			