

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	sj97904	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	04 Hour 00 Min 51 Sec
Total Counter :	5453084	Total Running Time :	2300 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	57	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.59	kN	No		
HEP :	22.0 %	9.00	kN	Yes 10	Rotations 20	Tablets
HCP :	2.5 %	7.56	kN	Yes 15	Times	
Ref :		7.38	kN			
LCP :	2.5 %	7.19	kN	Yes 15	Times	
LEP :	28.0 %	5.31	kN	Yes 15	Rotations 20	Tablets
LSP :	35.0 %	4.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.65	kN	Punch NO.;	23
SD :	3.80	%	Max :	1.93	kN	Punch NO.;	52
Mean Main Pressure :	7.48	kN	Min :	6.18	kN	Punch NO.;	25
SD :	8.00	%	Max :	8.56	kN	Punch NO.;	43
Filling Depth :	Increase ; 155	Times	Decrease ;	223	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.40	mm	Pre Thickness ;	1.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	3.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.38	kN	Max Punch ;	11
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	37
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	5453084	Tablets			
A.W.C Counter :	5420466	Tablets			
HEP :	2169 (0.0%)	Tablets	LEP :	64461 (1.2%)	Tablets
GOOD :	5353836 (98.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PROPRA 10MG STPJ2A00
User ID :	sj97904	Batch NO. :	PJM2500610
Print Interval :	50000 Tablets	Running Time :	04 Hour 00 Min 51 Sec
Total Counter :	5453084	Total Running Time :	2300 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	31	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6400000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		190	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	10.49	kN	No		
HEP :	20.0 %	10.07	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	8.56	kN	Yes 20	Times	
Ref :		8.39	kN			
LCP :	2.0 %	8.22	kN	Yes 20	Times	
LEP :	20.0 %	6.71	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	6.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.81	kN	Min :	1.74	kN	Punch NO.;	22
SD :	1.60	%	Max :	1.89	kN	Punch NO.;	56
Mean Main Pressure :	8.45	kN	Min :	7.54	kN	Punch NO.;	17
SD :	4.80	%	Max :	9.56	kN	Punch NO.;	2
Filling Depth :	Increase ;	322	Times	Decrease ;	349	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.55	mm	Pre Thickness ;	1.55	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	4.07	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.38	kN	Max Punch ;	11
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	37
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	5453084	Tablets			
A.W.C Counter :	5420466	Tablets			
HEP :	2169 (0.0%)	Tablets	LEP :	64461 (1.2%)	Tablets
GOOD :	5353836 (98.8%)	Tablets			