

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 26 Sec
Total Counter :	50082	Total Running Time :	2305 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.74	kN	No		
HEP :	25.0 %	25.71	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.98	kN	Yes 15	Times	
Ref :		20.57	kN			
LCP :	2.0 %	20.16	kN	Yes 15	Times	
LEP :	25.0 %	15.43	kN	Yes 15	Rotations 20	Tablets
LSP :	35.0 %	13.37	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.63	kN	Min :	1.55	kN	Punch NO.;	52
SD :	2.00	%	Max :	1.71	kN	Punch NO.;	17
Mean Main Pressure :	20.70	kN	Min :	19.20	kN	Punch NO.;	47
SD :	3.50	%	Max :	22.37	kN	Punch NO.;	17
Filling Depth :	Increase ; 21	Times	Decrease ;	20	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.20	mm
Filling Depth :	6.84	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.833	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.12	kN	Max Punch ;	37
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	9
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	50082	Tablets			
A.W.C Counter :	43749	Tablets			
HEP :	246 (0.6%)	Tablets	LEP :	66 (0.2%)	Tablets
GOOD :	43437 (99.3%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 26 Sec
Total Counter :	50082	Total Running Time :	2305 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.86	kN	No		
HEP :	25.0 %	26.86	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.92	kN	Yes 20	Times	
Ref :		21.49	kN			
LCP :	2.0 %	21.06	kN	Yes 20	Times	
LEP :	25.0 %	16.12	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.12	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.62	kN	Min :	1.58	kN	Punch NO.;	18
SD :	1.10	%	Max :	1.66	kN	Punch NO.;	37
Mean Main Pressure :	21.33	kN	Min :	19.10	kN	Punch NO.;	9
SD :	4.40	%	Max :	23.95	kN	Punch NO.;	41
Filling Depth :	Increase ;	29	Times	Decrease ;	25	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.833	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	47
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	9
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	50082	Tablets			
A.W.C Counter :	43749	Tablets			
HEP :	246 (0.6%)	Tablets	LEP :	66 (0.2%)	Tablets
GOOD :	43437 (99.3%)	Tablets			