

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	gp98929	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	08 Hour 59 Min 11 Sec
Total Counter :	1403010	Total Running Time :	2313 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	57	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.36	kN	No		
HEP :	20.0 %	25.31	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.51	kN	Yes 20	Times	
Ref :		21.09	kN			
LCP :	2.0 %	20.67	kN	Yes 20	Times	
LEP :	20.0 %	16.87	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	15.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
SD :	0.00	%	Max :	0.00	kN	Punch NO.;	1
Mean Main Pressure :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
SD :	0.00	%	Max :	0.00	kN	Punch NO.;	1
Filling Depth :	Increase ; 0	Times	Decrease ; 0	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	9.05	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.843	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	1403010	Tablets			
A.W.C Counter :	1380536	Tablets			
HEP :	1629 (0.1%)	Tablets	LEP :	705 (0.1%)	Tablets
GOOD :	1378202 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	gp98929	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	08 Hour 59 Min 11 Sec
Total Counter :	1403010	Total Running Time :	2313 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.74	kN	No		
HEP :	20.0 %	26.63	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	22.64	kN	Yes 20	Times	
Ref :		22.19	kN			
LCP :	2.0 %	21.75	kN	Yes 20	Times	
LEP :	20.0 %	17.75	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.64	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
SD :	0.00	%	Max :	0.00	kN	Punch NO.;	1
Mean Main Pressure :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
SD :	0.00	%	Max :	0.00	kN	Punch NO.;	1
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	8.91	mm	Current Cam :	Cam C	
Main Air pressure :	0.843	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	1403010	Tablets			
A.W.C Counter :	1380536	Tablets			
HEP :	1629 (0.1%)	Tablets	LEP :	705 (0.1%)	Tablets
GOOD :	1378202 (99.8%)	Tablets			