

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	10 Hour 28 Min 40 Sec
Total Counter :	1611480	Total Running Time :	2315 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	57	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.43	kN	No		
HEP :	20.0 %	25.37	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	21.56	kN	Yes 20	Times	
Ref :		21.14	kN			
LCP :	2.0 %	20.72	kN	Yes 20	Times	
LEP :	20.0 %	16.91	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	15.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.15	kN	Punch NO.;	47
SD :	4.70	%	Max :	2.74	kN	Punch NO.;	34
Mean Main Pressure :	21.43	kN	Min :	18.95	kN	Punch NO.;	47
SD :	4.80	%	Max :	23.55	kN	Punch NO.;	34
Filling Depth :	Increase ;	216	Times	Decrease ;	235	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.93	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.22	kN	Max Punch ;	32
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	35
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1611480	Tablets			
A.W.C Counter :	1587348	Tablets			
HEP :	2423 (0.2%)	Tablets	LEP :	728 (0.0%)	Tablets
GOOD :	1584197 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	os190259	Batch NO. :	IUM2500940
Print Interval :	50000 Tablets	Running Time :	10 Hour 28 Min 40 Sec
Total Counter :	1611480	Total Running Time :	2315 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	50	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.73	kN	No		
HEP :	20.0 %	25.66	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.81	kN	Yes 20	Times	
Ref :		21.38	kN			
LCP :	2.0 %	20.95	kN	Yes 20	Times	
LEP :	20.0 %	17.10	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.04	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.72	kN	Min :	2.51	kN	Punch NO.;	10
SD :	3.70	%	Max :	3.00	kN	Punch NO.;	7
Mean Main Pressure :	22.02	kN	Min :	19.78	kN	Punch NO.;	10
SD :	4.50	%	Max :	24.72	kN	Punch NO.;	7
Filling Depth :	Increase ;	190	Times	Decrease ;	174	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.21	kN	Max Punch ;	32
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	35
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1611480	Tablets			
A.W.C Counter :	1587348	Tablets			
HEP :	2423 (0.2%)	Tablets	LEP :	728 (0.0%)	Tablets
GOOD :	1584197 (99.8%)	Tablets			