

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2501140
Print Interval :	50000 Tablets	Running Time :	05 Hour 25 Min 53 Sec
Total Counter :	689264	Total Running Time :	2339 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.04	kN	No		
HEP :	20.0 %	25.96	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.07	kN	Yes 20	Times	
Ref :		21.64	kN			
LCP :	2.0 %	21.20	kN	Yes 20	Times	
LEP :	20.0 %	17.31	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	16.23	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.53	kN	Min :	2.39	kN	Punch NO.;	29
SD :	3.00	%	Max :	2.73	kN	Punch NO.;	51
Mean Main Pressure :	22.35	kN	Min :	20.86	kN	Punch NO.;	33
SD :	3.60	%	Max :	24.51	kN	Punch NO.;	7
Filling Depth :	Increase ; 74	Times	Decrease ; 78	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.48	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.16	kN	Max Punch ;	23
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	689264	Tablets			
A.W.C Counter :	687388	Tablets			
HEP :	22 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	687365 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2501140
Print Interval :	50000 Tablets	Running Time :	05 Hour 25 Min 53 Sec
Total Counter :	689264	Total Running Time :	2339 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.24	kN	No		
HEP :	20.0 %	25.19	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.41	kN	Yes 20	Times	
Ref :		20.99	kN			
LCP :	2.0 %	20.57	kN	Yes 20	Times	
LEP :	20.0 %	16.79	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	15.74	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.78	kN	Min :	2.53	kN	Punch NO.;	37
SD :	3.40	%	Max :	2.94	kN	Punch NO.;	22
Mean Main Pressure :	21.30	kN	Min :	18.90	kN	Punch NO.;	37
SD :	4.20	%	Max :	22.91	kN	Punch NO.;	50
Filling Depth :	Increase ;	71	Times	Decrease ;	78	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.17	kN	Max Punch ;	23
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	689264	Tablets			
A.W.C Counter :	687388	Tablets			
HEP :	22 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	687365 (100.0%)	Tablets			