

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIQ2A00
User ID :	rp98927	Batch NO. :	IQM2502340
Print Interval :	50000 Tablets	Running Time :	04 Hour 45 Min 21 Sec
Total Counter :	450134	Total Running Time :	2354 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		810000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	53.99	kN	No		
HEP :	20.0 %	51.84	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	44.06	kN	Yes 20	Times	
Ref :		43.20	kN			
LCP :	2.0 %	42.33	kN	Yes 20	Times	
LEP :	20.0 %	34.56	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	32.40	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	13.82	kN	Min :	11.91	kN	Punch NO.;	14
		5.10	%	Max :	15.56	kN	Punch NO.;	37
Mean Main Pressure :		43.03	kN	Min :	40.55	kN	Punch NO.;	20
	SD :	2.30	%	Max :	45.22	kN	Punch NO.;	37
Filling Depth :	Increase ;	9	Times	Decrease ;	29	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	6.90	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.28	kN	Max Punch ;	3
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450134	Tablets			
A.W.C Counter :	445019	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	119 (0.0%)	Tablets
GOOD :	444892 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIQ2A00
User ID :	rp98927	Batch NO. :	IQM2502340
Print Interval :	50000 Tablets	Running Time :	04 Hour 45 Min 21 Sec
Total Counter :	450134	Total Running Time :	2354 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		810000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	51.37	kN	No		
HEP :	20.0 %	49.32	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	41.92	kN	Yes 20	Times	
Ref :		41.10	kN			
LCP :	2.0 %	40.28	kN	Yes 20	Times	
LEP :	20.0 %	32.88	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	11.38	kN	Min :	9.43	kN	Punch NO.;	15
		10.00	%	Max :	14.68	kN	Punch NO.;	37
Mean Main Pressure :		40.58	kN	Min :	37.20	kN	Punch NO.;	15
	SD :	4.40	%	Max :	45.27	kN	Punch NO.;	37
Filling Depth :	Increase ;	44	Times	Decrease ;	8	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	6.99	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.27	kN	Max Punch ;	3
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450134	Tablets			
A.W.C Counter :	445072	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	119 (0.0%)	Tablets
GOOD :	444945 (100.0%)	Tablets			