

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIQ2A00
User ID :	sj97904	Batch NO. :	IQM2502340
Print Interval :	50000 Tablets	Running Time :	08 Hour 31 Min 07 Sec
Total Counter :	805680	Total Running Time :	2358 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	152	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		810000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	53.68	kN	No		
HEP :	20.0 %	51.53	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	43.80	kN	Yes 20	Times	
Ref :		42.94	kN			
LCP :	2.0 %	42.08	kN	Yes 20	Times	
LEP :	20.0 %	34.35	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	32.21	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	13.46	kN	Min :	11.46	kN	Punch NO.;	14
		9.80	%	Max :	16.03	kN	Punch NO.;	46
Mean Main Pressure :		43.47	kN	Min :	39.96	kN	Punch NO.;	14
	SD :	4.60	%	Max :	47.26	kN	Punch NO.;	46
Filling Depth :	Increase ;	14	Times	Decrease ;	3	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	7.33	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.824	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	20
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	17
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	805680	Tablets			
A.W.C Counter :	798187	Tablets			
HEP :	32 (0.0%)	Tablets	LEP :	120 (0.0%)	Tablets
GOOD :	798035 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIQ2A00
User ID :	sj97904	Batch NO. :	IQM2502340
Print Interval :	50000 Tablets	Running Time :	08 Hour 31 Min 07 Sec
Total Counter :	805680	Total Running Time :	2358 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	150	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		810000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	54.10	kN	No		
HEP :	20.0 %	51.93	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	44.14	kN	Yes 20	Times	
Ref :		43.28	kN			
LCP :	2.0 %	42.41	kN	Yes 20	Times	
LEP :	20.0 %	34.62	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	32.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	12.65	kN	Min :	10.22	kN	Punch NO.;	9
		11.50	%	Max :	17.25	kN	Punch NO.;	46
Mean Main Pressure :		42.86	kN	Min :	39.62	kN	Punch NO.;	9
	SD :	4.40	%	Max :	48.30	kN	Punch NO.;	46
Filling Depth :	Increase ;	7	Times	Decrease ;	2	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	7.10	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.823	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.53	kN	Max Punch ;	19
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	17
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	805680	Tablets			
A.W.C Counter :	798187	Tablets			
HEP :	32 (0.0%)	Tablets	LEP :	120 (0.0%)	Tablets
GOOD :	798035 (100.0%)	Tablets			