

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502710
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 44 Sec
Total Counter :	150018	Total Running Time :	2359 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	162	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		660000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	45.47	kN	No		
HEP :	20.0 %	43.65	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	37.10	kN	Yes 20	Times	
Ref :		36.37	kN			
LCP :	2.0 %	35.64	kN	Yes 20	Times	
LEP :	20.0 %	29.10	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	27.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.11	kN	Min :	2.03	kN	Punch NO.;	30
SD :	1.40	%	Max :	2.21	kN	Punch NO.;	6
Mean Main Pressure :	36.49	kN	Min :	34.96	kN	Punch NO.;	33
SD :	2.00	%	Max :	38.33	kN	Punch NO.;	13
Filling Depth :	Increase ; 19	Times	Decrease ; 9	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	10.69	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	29
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	150018	Tablets			
A.W.C Counter :	146314	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	146275 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502710
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 44 Sec
Total Counter :	150018	Total Running Time :	2359 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	163	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	46.54	kN	No		
HEP :	20.0 %	44.67	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	37.97	kN	Yes 20	Times	
Ref :		37.23	kN			
LCP :	2.0 %	36.48	kN	Yes 20	Times	
LEP :	20.0 %	29.78	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	27.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.24	kN	Min :	2.18	kN	Punch NO.;	20
		1.70	%	Max :	2.35	kN	Punch NO.;	40
Mean Main Pressure :		37.29	kN	Min :	35.30	kN	Punch NO.;	29
	SD :	2.60	%	Max :	40.98	kN	Punch NO.;	53
Filling Depth :	Increase ;	7	Times	Decrease ;	6	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.70	mm	Main Thickness ;	3.70	mm
Filling Depth :	10.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	29
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	150018	Tablets			
A.W.C Counter :	146314	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	146275 (100.0%)	Tablets			