

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502810
Print Interval :	50000 Tablets	Running Time :	03 Hour 31 Min 48 Sec
Total Counter :	332110	Total Running Time :	2368 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	216	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	44.78	kN	No		
HEP :	20.0 %	42.99	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	36.54	kN	Yes 20	Times	
Ref :		35.82	kN			
LCP :	2.0 %	35.11	kN	Yes 20	Times	
LEP :	20.0 %	28.66	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	26.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.05	kN	Min :	1.99	kN	Punch NO.;	29
		1.10	%	Max :	2.12	kN	Punch NO.;	6
Mean Main Pressure :		35.56	kN	Min :	33.85	kN	Punch NO.;	43
	SD :	2.10	%	Max :	37.08	kN	Punch NO.;	19
Filling Depth :	Increase ;	36	Times	Decrease ;	41	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.65	mm	Main Thickness ;	3.66	mm
Filling Depth :	10.92	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	32
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	332110	Tablets			
A.W.C Counter :	326851	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	326851 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502810
Print Interval :	50000 Tablets	Running Time :	03 Hour 31 Min 48 Sec
Total Counter :	332110	Total Running Time :	2368 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	199	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	45.17	kN	No		
HEP :	20.0 %	43.36	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	36.86	kN	Yes 20	Times	
Ref :		36.13	kN			
LCP :	2.0 %	35.41	kN	Yes 20	Times	
LEP :	20.0 %	28.91	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	27.10	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.15	kN	Punch NO.;	30
SD :	1.50	%	Max :	2.29	kN	Punch NO.;	1
Mean Main Pressure :	36.27	kN	Min :	34.70	kN	Punch NO.;	43
SD :	2.70	%	Max :	39.21	kN	Punch NO.;	53
Filling Depth :	Increase ; 30	Times	Decrease ;	22	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	33	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.84	mm	Main Thickness ;	3.85	mm
Filling Depth :	10.38	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	32
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	332110	Tablets			
A.W.C Counter :	326904	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	326904 (100.0%)	Tablets			