

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	pb97604	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	01 Hour 59 Min 26 Sec
Total Counter :	200064	Total Running Time :	2373 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	163	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	49.24	kN	No		
HEP :	20.0 %	47.27	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	40.18	kN	Yes 20	Times	
Ref :		39.39	kN			
LCP :	2.0 %	38.60	kN	Yes 20	Times	
LEP :	20.0 %	31.51	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.54	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.11	kN	Min :	2.06	kN	Punch NO.;	30
SD :	1.10	%	Max :	2.16	kN	Punch NO.;	42
Mean Main Pressure :	38.87	kN	Min :	37.20	kN	Punch NO.;	33
SD :	1.90	%	Max :	40.62	kN	Punch NO.;	13
Filling Depth :	Increase ; 67	Times	Decrease ;	152	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	50880	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	10.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.814	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	17
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.02	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	200064	Tablets			
A.W.C Counter :	99129	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	99129 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pb97604 Print Interval : 50000 Tablets Total Counter : 200064 Station : Station 2	Product Name : Leveti1000mgSTLC2D00 Batch NO. : LCM2502910 Running Time : 01 Hour 59 Min 26 Sec Total Running Time : 2373 Hour 58 Min
--	--

Setting Value

Feeder :	Auto ;	162	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		660000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.28	kN	No		
HEP :	20.0 %	48.27	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	41.03	kN	Yes 20	Times	
Ref :		40.22	kN			
LCP :	2.0 %	39.42	kN	Yes 20	Times	
LEP :	20.0 %	32.18	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.24	kN	Min :	2.18	kN	Punch NO.;	29
		1.40	%	Max :	2.33	kN	Punch NO.;	40
Mean Main Pressure :		39.70	kN	Min :	38.22	kN	Punch NO.;	33
	SD :	2.50	%	Max :	42.87	kN	Punch NO.;	53
Filling Depth :	Increase ;	56	Times	Decrease ;	92	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	50880	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.75	mm	Main Thickness ;	3.76	mm
Filling Depth :	10.24	mm	Current Cam :	Cam C	
Main Air pressure :	0.814	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	32
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.02	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	200064	Tablets			
A.W.C Counter :	99129	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	99129 (100.0%)	Tablets			