

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	04 Hour 02 Min 58 Sec
Total Counter :	400148	Total Running Time :	2376 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.12	kN	No		
HEP :	20.0 %	46.20	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.27	kN	Yes 20	Times	
Ref :		38.50	kN			
LCP :	2.0 %	37.73	kN	Yes 20	Times	
LEP :	20.0 %	30.80	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.15	kN	Min :	2.10	kN	Punch NO.;	30
		0.90	%	Max :	2.19	kN	Punch NO.;	46
Mean Main Pressure :	SD :	39.11	kN	Min :	37.49	kN	Punch NO.;	41
		1.90	%	Max :	40.55	kN	Punch NO.;	11
Filling Depth :	Increase ;	71	Times	Decrease ;	165	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	10.55	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	17
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	400148	Tablets			
A.W.C Counter :	206242	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	206242 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	04 Hour 02 Min 58 Sec
Total Counter :	400148	Total Running Time :	2376 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.01	kN	No		
HEP :	20.0 %	48.01	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	40.81	kN	Yes 20	Times	
Ref :		40.01	kN			
LCP :	2.0 %	39.21	kN	Yes 20	Times	
LEP :	20.0 %	32.01	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.01	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.29	kN	Min :	2.22	kN	Punch NO.;	30
		1.50	%	Max :	2.36	kN	Punch NO.;	21
Mean Main Pressure :		40.17	kN	Min :	38.22	kN	Punch NO.;	15
	SD :	2.40	%	Max :	43.01	kN	Punch NO.;	13
Filling Depth :	Increase ;	61	Times	Decrease ;	95	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.75	mm	Main Thickness ;	3.76	mm
Filling Depth :	10.31	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	17
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	400148	Tablets			
A.W.C Counter :	206242	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	206242 (100.0%)	Tablets			