

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	05 Hour 06 Min 43 Sec
Total Counter :	500172	Total Running Time :	2377 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.12	kN	No		
HEP :	20.0 %	46.20	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.27	kN	Yes 20	Times	
Ref :		38.50	kN			
LCP :	2.0 %	37.73	kN	Yes 20	Times	
LEP :	20.0 %	30.80	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.10	kN	Min :	2.04	kN	Punch NO.;	30
		1.30	%	Max :	2.15	kN	Punch NO.;	5
Mean Main Pressure :	SD :	38.79	kN	Min :	36.96	kN	Punch NO.;	33
		2.00	%	Max :	40.39	kN	Punch NO.;	11
Filling Depth :	Increase ;	71	Times	Decrease ;	184	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	9.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	500172	Tablets			
A.W.C Counter :	306306	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	306306 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2502910
Print Interval :	50000 Tablets	Running Time :	05 Hour 06 Min 43 Sec
Total Counter :	500172	Total Running Time :	2377 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	170	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.01	kN	No		
HEP :	20.0 %	48.01	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	40.81	kN	Yes 20	Times	
Ref :		40.01	kN			
LCP :	2.0 %	39.21	kN	Yes 20	Times	
LEP :	20.0 %	32.01	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.01	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.23	kN	Min :	2.17	kN	Punch NO.;	30
		1.40	%	Max :	2.30	kN	Punch NO.;	21
Mean Main Pressure :	SD :	39.97	kN	Min :	38.34	kN	Punch NO.;	33
		2.50	%	Max :	43.18	kN	Punch NO.;	13
Filling Depth :	Increase ;	61	Times	Decrease ;	100	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.75	mm	Main Thickness ;	3.76	mm
Filling Depth :	10.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	500172	Tablets			
A.W.C Counter :	306306	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	306306 (100.0%)	Tablets			