

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	vg96371	Batch NO. :	LCM2503010
Print Interval :	50000 Tablets	Running Time :	02 Hour 39 Min 28 Sec
Total Counter :	250064	Total Running Time :	2381 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	165	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	49.21	kN	No		
HEP :	20.0 %	47.24	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	40.16	kN	Yes 20	Times	
Ref :		39.37	kN			
LCP :	2.0 %	38.58	kN	Yes 20	Times	
LEP :	20.0 %	31.49	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.53	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.16	kN	Min :	2.11	kN	Punch NO.;	30
		1.10	%	Max :	2.22	kN	Punch NO.;	43
Mean Main Pressure :		39.67	kN	Min :	37.95	kN	Punch NO.;	33
	SD :	2.00	%	Max :	41.41	kN	Punch NO.;	37
Filling Depth :	Increase ;	10	Times	Decrease ;	13	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.97	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	13
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	250064	Tablets			
A.W.C Counter :	249027	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	249027 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	vg96371	Batch NO. :	LCM2503010
Print Interval :	50000 Tablets	Running Time :	02 Hour 39 Min 28 Sec
Total Counter :	250064	Total Running Time :	2381 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	167	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	49.60	kN	No		
HEP :	20.0 %	47.62	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	40.47	kN	Yes 20	Times	
Ref :		39.68	kN			
LCP :	2.0 %	38.89	kN	Yes 20	Times	
LEP :	20.0 %	31.74	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	29.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.28	kN	Min :	2.21	kN	Punch NO.;	4
		1.30	%	Max :	2.35	kN	Punch NO.;	21
Mean Main Pressure :		39.62	kN	Min :	37.92	kN	Punch NO.;	43
	SD :	2.10	%	Max :	41.70	kN	Punch NO.;	37
Filling Depth :	Increase ;	0	Times	Decrease ;	11	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.79	mm	Main Thickness ;	3.80	mm
Filling Depth :	10.14	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.762	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	13
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	250064	Tablets			
A.W.C Counter :	249027	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	249027 (100.0%)	Tablets			