

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2503210
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 32 Sec
Total Counter :	200036	Total Running Time :	2394 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	181	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.26	kN	No		
HEP :	20.0 %	46.33	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.38	kN	Yes 20	Times	
Ref :		38.60	kN			
LCP :	2.0 %	37.83	kN	Yes 20	Times	
LEP :	20.0 %	30.88	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.10	kN	Min :	2.02	kN	Punch NO.;	30
SD :	1.30	%	Max :	2.16	kN	Punch NO.;	42
Mean Main Pressure :	37.91	kN	Min :	35.85	kN	Punch NO.;	43
SD :	1.90	%	Max :	39.59	kN	Punch NO.;	1
Filling Depth :	Increase ; 108	Times	Decrease ;	126	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	10.18	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.16	kN	Max Punch ;	6
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	200036	Tablets			
A.W.C Counter :	198098	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	198098 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	rp98927	Batch NO. :	LCM2503210
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 32 Sec
Total Counter :	200036	Total Running Time :	2394 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	185	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	51.35	kN	No		
HEP :	20.0 %	49.30	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	41.90	kN	Yes 20	Times	
Ref :		41.08	kN			
LCP :	2.0 %	40.26	kN	Yes 20	Times	
LEP :	20.0 %	32.87	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.81	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.34	kN	Min :	2.27	kN	Punch NO.;	30
SD :	1.40	%	Max :	2.41	kN	Punch NO.;	10
Mean Main Pressure :	40.44	kN	Min :	38.70	kN	Punch NO.;	15
SD :	2.00	%	Max :	42.60	kN	Punch NO.;	53
Filling Depth :	Increase ; 89	Times	Decrease ;	128	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.78	mm	Main Thickness ;	3.79	mm
Filling Depth :	10.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.16	kN	Max Punch ;	6
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	200036	Tablets			
A.W.C Counter :	198098	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	198098 (100.0%)	Tablets			